



SHENZHEN YARUI TESTING CO., LTD.

Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China

Tel : +86-755-27912080

Fax: +86-755-27916936

FCC Part 15, Subpart B, Class B(sDoC)

TEST REPORT

Product name: Jump rope machine
Trademark: N/A
Model No.: SK-2
Test Standards: **FCC Part 15, Subpart B, Class B(sDoC), ANSI C63.4-2014**
Applicant: Shenzhen Ruihai Medical Equipment Co.,Ltd
Address of applicant: F1-4 Building 1#, Longfu Industrial Zone, Huarong Rd, Tongsheng Community, Dalang Subdistrict, Longhua District, Shenzhen, China
Date of Date: Jun.20, 2022- Jun.24, 2022
Date of issue.: Jun.24, 2022
Report No.: YRT202206248F

Test result :	Pass *
---------------	--------

* In the configuration tested, the EUT complied with the standards specified above



The FCC mark as shown above can be used, The Sample was tested to conform to the applicable FCC Rules and Regulations. The method of testing was in accordance to the most accurate measurement standards possible, and that all necessary steps have been enforced to assure that all production units of the same equipment will continue to comply with the Federal Communications Commission's requirements.

TEST Report

Equipment	Jump rope machine				
Model Name	SK-2				
Adding Model(s):	N/A				
Model Difference	N/A				
Manufacturer	Shenzhen Ruihai Medical Equipment Co.,Ltd				
Manufacturer Address	F1-4 Building 1#, Longfu Industrial Zone, Huarong Rd, Tongsheng Community, Dalang Subdistrict, Longhua District, Shenzhen, China				
Product Description	The EUT is a Jump rope machine <table><tr><td>Operating frequency:</td><td>N/A</td></tr><tr><td>Connecting I/O port:</td><td>N/A</td></tr></table> Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	Operating frequency:	N/A	Connecting I/O port:	N/A
Operating frequency:	N/A				
Connecting I/O port:	N/A				
Power Rating	Input: 6VDC 200mA				

Testing Engineer


:



(David Zhong)

Reviewed By:

:



(Tony Wang)

Approved Signatory

:



(Lily Yu)

It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by YRT. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to YRT within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com



TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION	4
2 EUT DESCRIPTION	5
3 TEST METHODOLOGY	6
3.1. DECISION OF FINAL TEST MODE	6
3.2. EUT SYSTEM OPERATION	6
4 SETUP OF EQUIPMENT UNDER TEST	7
4.1. DESCRIPTION OF SUPPORT UNITS	7
4.2. CONFIGURATION OF SYSTEM UNDER TEST	7
5 FACILITIES AND MEASUREMENT UNCERTAINTY	8
5.1. FACILITIES	8
5.2. MEASUREMENT UNCERTAINTY	8
6 CONDUCTED EMISSION MEASUREMENT	9
6.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
6.2. TEST INSTRUMENTS	9
6.3. TEST PROCEDURES	10
6.4. TEST SETUP	11
6.5. TEST RESULTS	11
7 RADIATED EMISSION MEASUREMENT	12
7.1. LIMITS OF RADIATED EMISSION MEASUREMENT	12
7.2. TEST INSTRUMENTS	12
7.3. TEST PROCEDURES	13
7.4. TEST SETUP	15
7.5. TEST RESULTS	15
8. ATTACHMENT PHOTOGRAPHS OF EUT	18

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com

1 TEST RESULT CERTIFICATION

Product:	Jump rope machine
Model :	SK-2
Additional models :	--
Trade Mark:	N/A
Applicant:	Shenzhen Ruihai Medical Equipment Co.,Ltd F1-4 Building 1#, Longfu Industrial Zone, Huarong Rd, Tongsheng Community, Dalang Subdistrict, Longhua District, Shenzhen, China
Manufacturer:	Shenzhen Ruihai Medical Equipment Co.,Ltd F1-4 Building 1#, Longfu Industrial Zone, Huarong Rd, Tongsheng Community, Dalang Subdistrict, Longhua District, Shenzhen, China
Test Voltage:	Input: 6VDC 200mA

EMISSION			
Standard	Item	Result	Remarks
FCC Part 15, Subpart B, Class B(sDoC), ANSI C63.4-2014	Conducted (Main Port)	N/A	N/A
	Radiated	PASS	Meet Class B limit

- Note: 1. The test result judgment is decided by the limit of measurement standard
2. The information of measurement uncertainty is available upon the customer's request.

Deviation from Applicable Standard
None

The above equipment has been tested by Shenzhen YaRui Testing Technology Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com



2 EUT DESCRIPTION

Product	Jump rope machine
Model :	SK-2
Additional models :	--
Trade Mark	N/A
Applicant	Shenzhen Ruihai Medical Equipment Co.,Ltd
EUT Type	☒ Engineering Sample ☐ Product Sample ☐ Mass Product Sample
Serial Number	N/A
Power Rating	Input: 6VDC 200mA

I/O PORT

I/O PORT TYPES	Q'TY	TESTED WITH
N/A	N/A	N/A

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com

3 TEST METHODOLOGY

3.1. DECISION OF FINAL TEST MODE

The EUT was tested together with the thereafter additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The following test mode(s) were scanned during the preliminary test:

Pre-Test Mode		
Emission	Conducted Emission	Mode: Full Load
	Radiated Emission	Mode: Full Load

After the preliminary scan, the following test mode was found to produce the highest emission level.

The Worst Test Mode		
Emission	Conducted Emission	Mode: Full Load
	Radiated Emission	Mode: Full Load

Then, the EUT configuration and cable configuration of the above highest emission mode was chosen for all final test items.

3.2. EUT SYSTEM OPERATION

1. Set up EUT with the relative support equipments.
2. Make sure the EUT worked normally during the test.

4 SETUP OF EQUIPMENT UNDER TEST

4.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model No.	Serial No.	FCC ID	Trade Name	Data Cable	Power Cord
	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.2. CONFIGURATION OF SYSTEM UNDER TEST



(EUT: Jump rope machine)

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com

5 FACILITIES AND MEASUREMENT UNCERTAINTY

5.1. FACILITIES

All measurement facilities used to collect the measurement data are located at No.101, Yousong Road, Longhua District, Shenzhen, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency		Uncertainty
Conducted emissions	9kHz~30MHz		+/- 3.59dB
Radiated emissions	Horizontal	30MHz ~ 200MHz	+/- 4.77dB
		200MHz ~1000MHz	+/- 4.93dB
	Vertical	30MHz ~ 200MHz	+/- 5.04dB
		200MHz ~1000MHz	+/- 4.93dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com

6 CONDUCTED EMISSION MEASUREMENT

6.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from EUT or system shall not exceed the level of field strengths specified above.

6.2. TEST INSTRUMENTS

Conducted Emission Shielding Room Test Site 843				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	100005	Dec.26, 2022
LISN	AFJ	LS16	16010222119	Dec.26, 2022
LISN	Meestec	AN3016	04/10040	Dec.26, 2022

- NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to International system of unit (SI).
2. N.C.R = No Calibration Request.

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com

6.3.TEST PROCEDURES

Procedure of Preliminary Test

The EUT and Support equipment, if needed, was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor standing equipment, it is placed on the ground plane, which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in Item 3.1 were scanned during the preliminary test.

After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.


Procedure of Final Test

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

6.4. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

6.5. TEST RESULTS

N/A

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
 Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com

7 RADIATED EMISSION MEASUREMENT

7.1. LIMITS OF RADIATED EMISSION MEASUREMENT

Maximum permissible level of Radiated Emission measured at 10 meter

FREQUENCY (MHz)	dBuV/m (At 3m)
	Class B
30~88	40.00
88~216	43.50
216~960	46.00
960~1000	54.00

NOTE: (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).

7.2. TEST INSTRUMENTS

Radiated Emission Test Site 966				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	100005	Dec.26, 2022
Spectrum Analyzer	R&S	FSU	100114	Dec.26, 2022
Pre Amplifier	H.P.	HP8447E	2945A02715	Dec.26, 2022
Bilog Antenna	SUNOL Sciences	JB3	A021907	Dec.26, 2022
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	Dec.26, 2022
System-Controller	CCS	N/A	N/A	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to International system of unit (SI).

2. N.C.R = No Calibration Request.

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com

7.3. TEST PROCEDURES

Procedure of Preliminary Test

The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

Support equipment, if needed, was placed as per ANSI C63.4.

All I/O cables were positioned to simulate typical usage as per ANSI C63.4.

Mains cables, telephone lines or other connections to auxiliary equipment located outside the test are shall drape to the floor, be fitted with ferrite clamps or ferrite tubes placed on the floor at the point where the cable reaches the floor and then routed to the place where they leave the turntable. No extension cords shall be used to mains receptacle.

The antenna was placed at 10 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.

The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

The test mode(s) described in Item 3.1 were scanned during the preliminary test:

After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.

The EUT and worse cable configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for the final test.

When measuring emissions above 1GHz, the frequencies of maximum emission shall be determined by manually positioning the antenna close to the EUT and by moving the antenna over all sides of the EUT while observing a spectral display. It will be advantageous to have prior knowledge of the frequencies of emissions above 1GHz. If the EUT is a device with dimensions approximately equal to that of the measurement antenna beam width, the measurement antenna shall be aligned with the EUT.

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com

Procedure of Final Test

EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.

The Analyzer / Receiver scanned from 30MHz to 1000MHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and only Q.P. reading is presented.

For the measurement above 1GHz, use the cable, EUT arrangement, and mode of operation determined in the exploratory testing to produce the emission that has the highest amplitude relative to the limit.

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the antenna in the “cone of radiation” from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.

The antenna may have to be higher or lower than the EUT, depending on the EUT's size and mounting height, but the antenna should be restricted to a range of height of from 1m to 4m above the ground or reference ground plane.

If the transmission line for the measurement antenna restricts its range of height and polarization, the steps needed to ensure the correct measurement of the maximum emissions, shall be described in detail in the report of the measurements.

using the procedures above to measure with peak detector function, if the result comply with the average limit specified by the appropriate regulation, record the EUT arrangement, mode of operation, and cable positions used for final radiated emission measurement , this can be done with either diagrams or photographs.


Set the detector function of the measuring instrument to average mode, using the procedures above and remeasure only those emissions that complied with the peak limits but exceeded the average limits.

Recorded at least the six highest emissions.

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com

7.4. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.5. TEST RESULTS


Model No.	SK-2	Test Mode	Full Load
Environmental Conditions	26°C, 55% RH	6Db Bandwidth	120 KHz
Antenna Pole	Vertical / Horizontal	Antenna Distance	3m
Detector Function	Peak / Quasi-peak	Test Result	Pass

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	Vertical
Test Mode:	Full Load	Test Voltage :	DC 6V

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	129.9225	14.05	13.55	27.60	43.50	-15.90	peak			
2	154.2786	12.76	14.99	27.75	43.50	-15.75	peak			
3	305.6800	18.56	14.20	32.76	46.00	-13.24	peak			
4	316.5889	19.00	14.51	33.51	46.00	-12.49	peak			
5	528.2458	13.54	18.78	32.32	46.00	-13.68	peak			
6 *	689.5643	13.78	21.63	35.41	46.00	-10.59	peak			




SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	Horizontal
Test Mode:	Full Load	Test Voltage :	DC 6V

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		168.4138	14.31	14.21	28.52	43.50	-14.98			peak
2	*	305.6800	27.84	14.20	42.04	46.00	-3.96			peak
3		457.5073	20.77	17.63	38.40	46.00	-7.60			peak
4		689.5644	13.45	21.63	35.08	46.00	-10.92			peak
5		766.0571	14.76	22.71	37.47	46.00	-8.53			peak
6		854.0247	13.36	23.56	36.92	46.00	-9.08			peak



SHENZHEN YARUI TESTING CO., LTD.


Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China
Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com

8. ATTACHMENT PHOTOGRAPHS OF EUT

Photo 1



Photo 2



===== End of Test Report =====

SHENZHEN YARUI TESTING CO., LTD.

Address: Room 125, 1F, Building A, Jie Mei kang Creative Park, No. 57 Donghuan 2nd Road, Fukang Community, Longhua Street, Longhua District, Shenzhen City, Guangdong Province, China

Tel.: +86-755-27912080 Fax.: +86-755-27916936 Website: www.yarui-lab.com