

# MSDS Report

<b>Report No.:</b>	SZ1230620-35486E-SF-02	
<b>Applicant:</b>	Shenzhen Youmi Intelligent Technology Co., Ltd	
<b>Address:</b>	406-407 Jinqi Zhigu Building,4/F,1 Tangling Road Nanshan District,Shenzhen China	
<b>Sample name:</b>	Li-ion Polymer Battery	
<b>Model:</b>	BLG5	
<b>Testing laboratory:</b>	Bay Area Compliance Laboratories Corp. (Dongguan)	
<b>Address:</b>	No.12, Pulong East 1st Road, Tangxia, Dongguan, Guangdong, China.	
<b>Testing location:</b>	Room 301, No. 113 Pingkang Road, Dalang Town, Dongguan, Guangdong, China.	
<b>Written by:</b>	Bobby Chen	<i>Bobby Chen</i>
<b>Reviewed by:</b>	David Yang	
<b>Issued date:</b>	2023-07-27	

Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the specific product described herein. It must not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

## Section 1– Chemical Product and Company Identification

Product Name .....	Li-ion Polymer Battery
Trade Mark.....	<b>UMIDIGI</b>
Model .....	BLG5
Rating.....	3.85V, 5000mAh, 19.25Wh
Weight.....	About 67.53g
Dimension .....	Max: T:4.75mm,W:64.4, L:95.2mm
Factory's Name .....	<b>Shenzhenshi jiuliyuan Electronic Technology Co., Ltd.</b>
Address .....	201, Jiuli Yuan Factory, Building A, No. 470, Pingshan Jinbi Road, Biling Community, Biling Street, Pingshan District, Shenzhen, China
E-mail address .....	szjlydz168@163.com
Contact information .....	Tel:86-13751326145

## Section 2 – Hazards Identification

Preparation hazards and classification	Not dangerous with normal use. Do not dismantle, open or shorted Li-ion Battery. Exposure to the ingredients contained within or their ingredients products could be harmful.
Appearance, Color, and Odor	Solid object with no odor, silvery.
Primary Route(s) of Exposure	The chemicals are contained in sealed plastic casings. Exposure risks occur only when the battery has been mechanically, thermally, or electrically abused to the extent that it damages the housing. If this occurs, exposure to the electrolyte solution contained therein may occur through inhalation, ingestion, eye contact, and skin contact
Potential Health Effects:	<b>ACUTE (short term):</b> see Section 8 for exposure controls In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be corrosive and can cause burns.

Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the specific product described herein. It must not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

	<p><b>Inhalation:</b> Inhalation of materials from a sealed battery is not an expected route of exposure. Vapors or mists from a ruptured battery may cause respiratory irritation.</p> <p><b>Ingestion:</b> Swallowing of materials from a sealed battery is not an expected route of exposure. Swallowing the contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract.</p> <p><b>Skin:</b> Contact between the battery and skin will not cause any harm. Skin contact with contents of an open battery can cause severe irritation or burns to the skin.</p> <p><b>Eye:</b> Contact between the battery and the eye will not cause any harm. Eye contact with contents of an open battery can cause severe irritation or burns to the eye.</p> <p><b>CHRONIC (long term):</b> see Section 11 for additional toxicological data</p>
Medical Conditions Aggravated by Exposure	Not applicable
Reported as carcinogen	Not applicable

### Section 3 – Composition/Information on Ingredients

Hazardous Ingredients (Chemical Name)	Concentration or concentration ranges(%)	CAS Number
Lithium Cobalt Oxide (LiCoO <sub>2</sub> )	25-35	12190-79-3
Graphite (C)	15-20	7782-42-5
Polyvinylidene Fluoride (PVDF)	1-5	24937-79-9
Acetylene Black (SP)	0.5-3	1333-86-4
Aluminum (Al)	21-23	7429-90-5
Copper (Cu)	10-11	7440-50-8
Lithium hexafluorophosphate (LiPF <sub>6</sub> )	10-15	21324-40-3

**Note: CAS number is Chemical Abstract Service Registry Number.**

Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the specific product described herein. It must not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

## Section 4 – First-aid Measures

<b>Inhalation</b>	If contents of an opened battery are inhaled, remove source of contamination or move victim to fresh air. Obtain medical advice.
<b>Skin contact</b>	If skin contact with contents of an open battery occurs, as quickly as possible remove contaminated clothing, shoes and leather goods. Immediately flush with lukewarm, gently flowing water for at least 30 minutes. If irritation or pain persists, seek medical attention. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
<b>Eye contact</b>	If eye contact with contents of an open battery occurs, immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes while holding the eyelids open. Neutral saline solution may be used as soon as it is available. If necessary, continue flushing during transport to emergency care facility. Take care not to rinse contaminated water into the unaffected eye or onto face. Quickly transport victim to an emergency care facility.
<b>Ingestion</b>	If ingestion of contents of an open battery occurs, never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. Do not induce vomiting. Have victim drink 60 to 240mL of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water again. Quickly transport victim to an emergency care facility.

## Section 5 – Fire-fighting Measures

Flammable Properties	In the event that this battery has been ruptured, the electrolyte solution contain within the battery would be flammable. Like any sealed container, battery cells may rupture when exposed to excessive heat; this could result in the release of flammable or corrosive materials.
Suitable extinguishing Media	Use extinguishing media suitable for the materials that are burning.
Unsuitable extinguishing Media	Not available
Explosion Data	<b>Sensitivity to Mechanical Impact:</b> This may result in rupture in extreme cases <b>Sensitivity to Static Discharge:</b> Not Applicable
Specific Hazards arising from the chemical	Fires involving Li-ion Cell can be controlled with water. When water is used, however, hydrogen gas may evolve. In a confined space, hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended to

Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the specific product described herein. It must not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

	extinguish the fire.
Protective Equipment and precautions for firefighters	As for any fire, evacuate the area and fight the fire from a safe distance. Wear a pressure-demand, self-contained breathing apparatus and full protective gear. Fight fire from a protected location or a safe distance. Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.
NFPA	Health: 0 Flammability: 0 Instability: 0

## Section 6 – Accidental Release Measures

Personal Precautions, protective equipment, and emergency procedures	Restrict access to area until completion of clean-up. Do not touch the spilled material. Wear adequate personal protective equipment as indicated in Section 8.
Environmental Precautions	Prevent material from contaminating soil and from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.

## Section 7 – Handling and Storage

Handling	Don't handling Li-ion Battery with metalwork. Do not open, disassemble, crush or burn battery. Ensure good ventilation/ exhaustion at the workplace.Prevent formation of dust. Information about protection against explosions and fires: Keep ignition sources away-Do not smoke.
Storage	Short period less than 1 month: -20°C~+50°C, 45~75%RH Max; within 3 months: -10°C~+ 45°C, 45~75%RH Max; Long term within 1 year: -5°C~+25°C, 45~75%RH Max. The battery should be stored in a clean, dry and ventilated room with an ambient temperature of -5°C ~25°C, avoid contact with corrosive substances, and keep away from fire and heat sources. The battery is charged every three months during storage.

Note:The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the specific product described herein.It must not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

	Do not storage Li-ion Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects. Do not expose Li-ion Battery on heat or fire. Avoid storage in direct sunlight. Do not store together with oxidizing and acidic materials. Keep container tightly sealed.
--	--

## Section 8 – Exposure Controls and Personal Protection

Engineering Controls	Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor.  Keep away from heat and open flame. Store in a cool, dry place.
Personal Protective Equipment	<b>Respiratory Protection:</b> Not necessary under normal conditions. <b>Skin and body Protection:</b> Not necessary under normal conditions, Wear neoprene or nitrile rubber gloves if handling an open or leaking battery. <b>Hand protection:</b> Wear neoprene or natural rubber material gloves if handling an open or leaking battery. <b>Eye Protection:</b> Not necessary under normal conditions, Wear safety glasses if handling an open or leaking battery.
Other Protective Equipment	Have a safety shower and eye wash fountain readily available in the immediate work area.
Hygiene Measures	Do not eat, drink, or smoke in work area. Maintain good housekeeping.

## Section 9 – Physical and Chemical Properties

Physical State	Form: Solid
	Color: Silvery
	Odour: Odorless
Change in condition:	
pH, with indication of the concentration	Not applicable
Melting point/freezing point	Not available
Boiling Point, initial boiling point and Boiling range:	Not available
Flash Point	Not available
Upper/lower flammability or	Not available

Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the specific product described herein. It must not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

explosive limits	
Vapor Pressure:	Not applicable
Vapor Density: (Air=1)	Not applicable
Density/relative density	Not available
Solubility in Water:	Insoluble
n-octanol /water partition coefficient	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Odour threshold	Not available
Evaporation rate	Not available
Flammability (soil, gas)	Not available
Viscosity	Not applicable

## Section 10 – Stability and Reactivity

Stability	The product is stable under normal conditions.
Conditions to Avoid (e.g. static discharge, shock or vibration)	Do not subject Li-ion Battery to mechanical shock. Vibration encountered during transportation does not cause leakage, fire or explosion. Do not disassemble, crush, short or install with incorrect polarity. Avoid mechanical or electrical abuse.
Incompatible Materials	Not available
Hazardous Decomposition Products	This material may release toxic fumes if burned or exposed to fire
Possibility of Hazardous Reaction	Not available

## Section 11 – Toxicological Information

Irritation	Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory tract may occur.
Sensitization	Not available
Neurological Effects	Not available

Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the specific product described herein. It must not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

Teratogenicity	Not available
Reproductive Toxicity	Not available
Mutagenicity (Genetic Effects)	Not available
Toxicologically Synergistic Materials	Not available

## Section 12 – Ecological Information

General note:	Water hazard class 1(Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Anticipated behavior of a chemical product in environment/possible environmental impact/ecotoxicity	Not available
Mobility in soil	Not available
Persistence and Degradability	Not available
Bioaccumulation potential	Not available
Other Adverse Effects	Not available

## Section 13 – Disposal Considerations

Product disposal recommendation: Observe local, state and federal laws and regulations. Packaging disposal recommendation: Be aware discarded batteries may cause fire, tape the battery terminals to insulate them. Don't disassembly the battery. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local, state and federal laws and regulations.

## Section 14 – Transport Information

For the international transport of lithium batteries, they must comply with these regulations: The International Maritime Dangerous Goods (IMDG) Code by International Maritime Organization (IMO), Dangerous Goods Regulations (DGR) by International Air Transport Association (IATA) and Technical Instructions for the Safe Transport of Dangerous Goods by Air by International Civil Aviation Organization (ICAO). These regulations are based on the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria. Lithium batteries which meet the requirements of UN38.3 (UN Manual of Tests and Criteria, Part III, subsection 38.3) could be transported by air and by sea as ordinary goods, otherwise should be transported according to Class 9, Packing Group II /IB hazardous goods.



<b>UN Number</b>	
IATA	UN3481
IMO	UN3481
<b>UN Proper shipping name</b>	
IATA	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT
IMO	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT
<b>Transport hazard class</b>	
IATA	9
IMO	9

**Transport information:**

The Li-ion Polymer Battery (BLG5) has passed the test UN38.3, according to the report number: SZ1230620-35486E-SF-01.

According to the Packing Instruction 967 II of IATA DGR Manual 64th Edition for transport by air.

According to the Special provision 188 of IMDG CODE (Amdt.40-20) for transport by sea.

## Section 15 – Regulatory Information

1. Dangerous Goods Regulations
2. Recommendations on the Transport of Dangerous Good-Model regulations (22th revised edition)
3. Recommendations on the Transport of Dangerous Good-Manual of Tests and Criteria
4. International Air Transport Association (IATA)
5. International Maritime Dangerous Goods (IMDG Code Amdt.40-20)
6. Technical Instructions for the Safe Transport of Dangerous Good
7. Classification and code of dangerous goods (GB 6944-2012)
8. 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)
9. Toxic Substance Control Act (TSCA)
10. Code of Federal Regulations
11. In accordance with all Federal, State and local laws

## Section 16 – Other Information

The information above is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. However we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, however arising from using the above information.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

**\*\*\*\*\*End of Report\*\*\*\*\***

Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the specific product described herein. It must not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).