



TEST REPORT ETSI EN 301 893 V2.1.1 (2017-05)

Report Reference No.: HK2101250269-3ER

Compiled by

(position+printed name+signature): Testing engineer Len Liao

Len Liao

Supervised by

(position+printed name+signature): Technique principal Sliver Wan

Sliver Wan

Approved by

(position+printed name+signature): Manager Jason Zhou

Jason Zhou

Date of issue: 2021/03/29

Representative Laboratory Name: Shenzhen HUAKE Testing Technology Co., Ltd.

Address: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Applicant's name: VIDEOSTRONG TECHNOLOGY CO., LIMITED

Address: 604, Lushi industrial Building, 28 District, Bao'an District, Shenzhen, China

Test specification:

Standard: ETSI EN 301 893 V2.1.1 (2017-05)

TRF Originator: Shenzhen HUAKE Testing Technology Co., Ltd.

Master TRF: Dated 2014-12

Shenzhen HUAKE Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: NOW

Trade Mark: MECOOL

Model/Type reference: KA2

List Model: KA1, KA1 PRO, KA2 PRO, KA3, KA3 PRO, KA5, KA5 PRO, KA6

Hardware version: V1.X

Software version: V4

Operation Frequency: From 5180MHz-5240MHz

Ratings: DC 5V From Adapter

Result: PASS

**TEST REPORT**

Test Report No. :	HK2101250269-3ER	2021/03/29
		Date of issue

Equipment under Test : NOW

Model /Type : KA2

Listed Models : KA1, KA1 PRO, KA2 PRO, KA3, KA3 PRO, KA5, KA5 PRO, KA6

Applicant : VIDEOSTRONG TECHNOLOGY CO., LIMITED

Address : 604, Lushi industrial Building, 28 District, Bao'an District, Shenzhen, China

Manufacturer : VIDEOSTRONG TECHNOLOGY CO., LIMITED

Address : 604, Lushi industrial Building, 28 District, Bao'an District, Shenzhen, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



**** Modified History ****

Revision	Description	Issued Data	Remark
Revision 1.0	Initial Test Report Release	2021/03/29	Jason Zhou



Contents

1.	TEST STANDARDS	5
2.	SUMMARY	6
2.1.	General Remarks	6
2.2.	Product Description	6
2.3.	Equipment Under Test	6
2.4.	EUT configuration	7
2.5.	Test summary	7
2.6.	Modifications	8
3.	TEST ENVIRONMENT	8
3.1.	Address of the test laboratory	8
3.2.	Environmental conditions	8
3.3.	Test Channels:	9
3.4.	Statement of the measurement uncertainty	9
3.5.	Equipments Used during the Test	10
4.	TEST CONDITIONS AND RESULTS	11
4.1.	Centre frequencies	11
4.2.	Nominal Channel Bandwidth and Occupied Channel Bandwidth	16
4.3.	RF output power, Transmit Power Control (TPC) and power density	23
4.3.1.	RF output power at the highest power - PH	24
4.3.2.	RF output power at the lowest power level of the TPC range - PL	27
4.4.	Power density	28
4.5.	Transmitter unwanted emissions	41
4.5.1.	Transmitter unwanted emissions outside the 5 GHz RLAN bands	41
4.5.2.	Transmitter unwanted emissions within the 5 GHz RLAN bands	44
4.6.	Receiver spurious emissions	51
4.7.	Dynamic Frequency Selection (DFS)	54
4.8.	Adaptivity	58
4.9.	Receiver Blocking	63
4.10.	User Access Restrictions	68
4.11.	Geo-location capability	69
5.	TEST SETUP PHOTOS OF THE EUT	70
6.	EXTERNAL AND INTERNAL PHOTOS OF THE EUT	71



1. TEST STANDARDS

The tests were performed according to following standards:

[ETSI EN 301 893 V2.1.1 \(2017-05\)](#)—5 GHz RLAN; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU



2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	2021/01/25
Testing commenced on	:	2021/01/25
Testing concluded on	:	2021/03/29

2.2. Product Description

Product Name:	NOW
Model/Type reference:	KA2
List Model:	KA1, KA1 PRO, KA2 PRO, KA3, KA3 PRO, KA5, KA5 PRO, KA6
Difference description	All model's the function, software and electric circuit are the same, only with a product color and model named different. Test sample model: KA2.
Power supply:	DC 5V From Adapter
POE Power information:	N/A
Antenna Type	Internal Antenna
Antenna Gain	3.0dBi
WLAN	Supported 802.11a/ 802.11n HT20/ 802.11n HT40/ 802.11ac HT20/ 802.11ac HT40/ 802.11ac HT80
Operation frequency	IEEE 802.11a:5180MHz-5240MHz IEEE 802.11n HT20/IEEE 802.11ac HT20:5180MHz-5240MHz IEEE 802.11n HT40/IEEE 802.11ac HT40:5190MHz-5230MHz IEEE 802.11ac HT80:5210MHz
Modulation Type	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11ac HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11ac HT40: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11ac HT80: OFDM (64QAM, 16QAM, QPSK,BPSK)
Remark: The products are identical in interior structure, electrical circuits and components, just model names are different.	

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

DC 5V From Adapter

**Channel list:**

Channel	Frequency (MHz)
36	5180
38	2190
40	5200
42	5210
44	5220
46	5230
48	5240

2.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○ /	M/N: /
	Manufacturer: /

2.5. Test summary

Test Item	Test Requirement ESTI EN301983	Verdict
Centre frequencies	Section 4.2.1	Pass
Nominal Channel Bandwidth and Occupied Channel Bandwidth	Section 4.2.2	Pass
RF output power, Transmit Power Control (TPC) and power density	Section 4.2.3	Pass
Transmitter unwanted emissions	Section 4.2.4	Pass
Receiver spurious emissions	Section 4.2.5	Pass
Dynamic Frequency Selection (DFS)	Section 4.2.6	N/A
Adaptivity (Channel Access Mechanism) 4.8.1 Applicability	Section 4.2.7	Pass
Receiver Blocking	Section 4.2.8	Pass
User Access Restrictions	Section 4.2.9	Pass
Geo-location capability	Section 4.2.10	N/A
Note:N/A Stands for "Not applicable"		



2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen HUAKE Testing Technology Co., Ltd.

1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature: 25 °C

High Temperature: 40 °C

Low Temperature: 10 °C

Normal Voltage : DC 5.0V

High Voltage:DC 5.5V

Low Voltage:DC 4.5V

Relative Humidity: 55 %

Air Pressure: 989 hPa



3.3. Test Channels:

Test	Clause	Test channels		
		Lower sub-band (5 150 MHz to 5 350 MHz)		Higher sub-band 5 725 MHz to 5 850 MHz
		5 150 MHz to 5 250 MHz	5 250 MHz to 5 350 MHz	
Centre frequencies	5.3.2	C7 (see note 1)		C8 (see note 1)
Occupied Channel Bandwidth	5.3.3	C7		C8
Power, power density	5.3.4	C1	C2	C3, C4
Transmitter unwanted emissions outside the 5 GHz RLAN bands	5.3.5	C7 (see note 1)		C8 (see note 1)
Transmitter unwanted emissions within the 5 GHz RLAN bands	5.3.6	C1	C2	C3, C4
Receiver spurious emissions	5.3.7	C7 (see note 1)		C8 (see note 1)
Transmit Power Control (TPC)	5.3.4	n.a. (see note 2)	C2 (see note 1)	C3, C4 (see note 1)
Dynamic Frequency Selection (DFS)	5.3.8	n.a. (see note 2)	C5	C6 (see note 3)
Adaptivity	5.3.9	C7		C8
C1, C3:	The lowest declared channel for every declared nominal channel bandwidth within this band. For the power density testing, it is sufficient to only perform this test using the lowest nominal channel bandwidth.			
C2, C4:	The highest declared channel for every declared nominal channel bandwidth within this band. For the power density testing, it is sufficient to only perform this test using the lowest nominal channel bandwidth.			
C5, C6:	One channel out of the declared channels for this frequency range. If more than one nominal channel bandwidth has been declared for this sub-band, testing shall be performed using the lowest and highest nominal channel bandwidth.			
C7, C8:	One channel out of the declared channels for this sub-band. For Occupied Channel Bandwidth, testing shall be repeated for every declared nominal channel bandwidth within this sub-band. For Adaptivity, testing shall be performed using the highest nominal channel bandwidth.			
NOTE 1:	In case of more than one channel plan has been declared, testing of these specific requirements need only be performed using one of the declared channel plans.			
NOTE 2:	Testing is not required for nominal channel bandwidths that fall completely within the frequency range 5 150 MHz to 5 250 MHz.			
NOTE 3:	Where the declared channel plan includes channels whose nominal channel bandwidth falls completely or partly within the 5 600 MHz to 5 650 MHz band, the tests for the <i>Channel Availability Check</i> (and where implemented, for the <i>Off-Channel CAC</i>) shall be performed on one of these channels in addition to a channel within the band 5 470 MHz to 5 600 MHz or within the band 5 650 MHz to 5 725 MHz.			

3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Global Test Service Co., Ltd quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen HUAKE laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Frequency error	25 Hz	(1)
Transmitter power conducted	0.57 Db	(1)
Transmitter power Radiated	2.20 Db	(1)
Conducted spurious emission	1.60 Db	(1)
Radiated spurious emission	2.20 Db	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

**3.5. Equipments Used during the Test**

Centre frequencies & RF output power & Power density & OCB & TPC						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
1	Spectrum analyzer	Agilent	N9020A	HKE-048	2020/06/18	2021/06/17
2	Signal generator	Agilent	N5182A	HKE-029	2020/06/18	2021/06/17
3	Signal generator	Agilent	83630A	HKE-028	2020/06/18	2021/06/17
4	RF automatic control unit	Tonscend	JS0806-2	HKE-060	2020/06/18	2021/06/17
5	Power Sensor	Agilent	E9300A	HKE-086	2020/06/18	2021/06/17
6	Temperature and humidity meter	Boyang	HTC-1	HKE-075	2020/06/18	2021/06/17

Adaptively & Receiver Blocking						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
1	Spectrum analyzer	R&S	FSP40	HKE-025	2020/06/18	2021/06/17
2	Wireless Communication Test Set	R&S	CMU200	HKE-026	2020/06/18	2021/06/17
3	Wireless Communication Test Set	R&S	CMW500	HKE-027	2020/06/18	2021/06/17
4	RF automatic control unit	Tonscend	JS0806-2	HKE-060	2020/06/18	2021/06/17

Transmitter spurious emissions & Receiver spurious emissions						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
1	Broadband antenna	Schwarzbeck	VULB 9163	HKE-012	2020/06/18	2021/06/17
2	Horn antenna	Schwarzbeck	9120D	HKE-013	2020/06/18	2021/06/17
3	Receiver	R&S	ESR-7	HKE-010	2020/06/18	2021/06/17
4	Position controller	Taiwan MF	MF7802	HKE-011	2020/06/18	2021/06/17
5	Preamplifier	EMCI	EMC05184 5SE	HKE-015	2020/06/18	2021/06/17
6	Preamplifier	Agilent	83051A	HKE-016	2020/06/18	2021/06/17
7	High pass filter unit	Tonscend	JS0806-F	HKE-055	2020/06/18	2021/06/17
8	Spectrum analyzer	Agilent	N9020A	HKE-048	2020/06/18	2021/06/17

The calibration interval is 1 year.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.



4. TEST CONDITIONS AND RESULTS

4.1. Centre frequencies

Limit

The actual centre frequency for any given channel declared by the manufacturer shall be maintained within the range $f_c \pm 20$ ppm.

Test Procedure

1. For equipment can operating without modulation
 - a Connected The UUT to the spectrum and operated in an unmodulated mode.
 - b Set the centre frequency of spectrum to the frequency which UUT operated.
 - c Max Hold and waiting the trace stabilized.
 - d Search the peak value of the power envelope and noted.
2. For equipment operating with modulation
 - a Connected The UUT to the spectrum.
 - b Set the centre frequency of spectrum to the frequency which UUT operated.
 - c Max Hold and waiting the trace stabilized.
 - d Search the peak value of the power envelope and noted.
 - e Move the marker in a positive frequency increment until the upper, (relative to the centre frequency), -10 dBc point is reached, note this point as f1.
 - f Move the marker in a negative frequency increment until the lower, (relative to the centre frequency), -10 dBc point is reached, note this point as f2.
 - g The centre frequency is calculated as $(f1 + f2) / 2$.
3. These measurements shall be performed under both normal and extreme test conditions.
4. One channel out of the declared channels for each sub-band shall be tested.

Test Results

**Ant 1**

Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 a	CH36/ 5180MHz	5179.976771	4.48
5.5	-10			5179.967796	6.22
	+40			5179.955931	8.51
4.5	-10			5179.967717	6.23
	+40			5179.950756	9.51
Limit				20 ppm	
Result				PASS	

Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 n HT 20	CH36/ 5180MHz	5179.961912	7.35
5.5	-10			5179.968262	6.13
	+40			5179.958107	8.09
4.5	-10			5179.969040	5.98
	+40			5179.954769	8.73
Limit				20 ppm	
Result				PASS	

Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 n HT 40	CH38/ 5190MHz	5189.966717	6.41
5.5	-10			5189.953578	8.94
	+40			5189.958697	7.96
4.5	-10			5189.947463	10.12
	+40			5189.947742	10.07
Limit				20 ppm	
Result				PASS	



Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 ac HT 20	CH36/ 5180MHz	5179.976747	4.49
5.5	-10			5179.955686	8.55
	+40			5179.954080	8.86
4.5	-10			5179.948854	9.87
	+40			5179.944388	10.74
Limit				20 ppm	
Result				PASS	

Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 ac HT 40	CH38/ 5190MHz	5189.951473	9.35
5.5	-10			5189.955704	8.53
	+40			5189.954339	8.80
4.5	-10			5189.942246	11.13
	+40			5189.946263	10.35
Limit				20 ppm	
Result				PASS	

Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 ac HT 80	CH42/ 5210MHz	5209.985650	2.75
5.5	-10			5209.952102	9.19
	+40			5209.950822	9.44
4.5	-10			5209.945659	10.43
	+40			5209.952288	9.16
Limit				20 ppm	
Result				PASS	



Ant 2

Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 a	CH36/ 5180MHz	5179.952495	9.17
5.5	-10			5179.965672	6.63
	+40			5179.953621	8.95
4.5	-10			5179.963594	7.03
	+40			5179.954067	8.87
Limit				20 ppm	
Result				PASS	

Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 n HT 20	CH36/ 5180MHz	5179.962268	7.28
5.5	-10			5179.967270	6.32
	+40			5179.953593	8.96
4.5	-10			5179.964923	6.77
	+40			5179.956377	8.42
Limit				20 ppm	
Result				PASS	

Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 n HT 40	CH38/ 5190MHz	5189.960919	7.53
5.5	-10			5189.953046	9.05
	+40			5189.956744	8.33
4.5	-10			5189.948697	9.88
	+40			5189.948547	9.91
Limit				20 ppm	
Result				PASS	



Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 ac HT 20	CH36/ 5180MHz	5179.949580	9.73
5.5	-10			5179.952771	9.12
	+40			5179.956312	8.43
4.5	-10			5179.949628	9.72
	+40			5179.944519	10.71
Limit				20 ppm	
Result				PASS	

Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 ac HT 40	CH38/ 5190MHz	5189.932078	13.09
5.5	-10			5189.955994	8.48
	+40			5189.953993	8.86
4.5	-10			5189.940925	11.38
	+40			5189.942635	11.05
Limit				20 ppm	
Result				PASS	

Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 ac HT 80	CH42/ 5210MHz	5209.969151	5.92
5.5	-10			5209.953764	8.87
	+40			5209.952843	9.05
4.5	-10			5209.948852	9.82
	+40			5209.951886	9.23
Limit				20 ppm	
Result				PASS	



4.2. Nominal Channel Bandwidth and Occupied Channel Bandwidth

LIMIT

The Nominal Channel Bandwidth for a single Operating Channel shall be 20 MHz

Alternatively, equipment may implement a lower Nominal Channel Bandwidth with a minimum of 5 MHz, providing they still comply with the Nominal Centre Frequencies defined in clause 4.2.1 (20 MHz raster).

The Occupied Channel Bandwidth shall be between 80 % and 100 % of the Nominal Channel Bandwidth. In case of smart antenna systems (devices with multiple transmit chains) each of the transmit chains shall meet this requirement.

The Occupied Channel Bandwidth might change with time/payload.

During a Channel Occupancy Time (COT), equipment may operate temporarily with an Occupied Channel Bandwidth of less than 80 % of its Nominal Channel Bandwidth with a minimum of 2 MHz

Test Procedure

1. Connect the UUT to the spectrum analyser and use the following settings:

Centre Frequency:	The centre frequency of the channel under test
Resolution Bandwidth:	100 kHz
Video Bandwidth:	300 kHz
Frequency Span:	2 × Nominal Bandwidth (e.g. 40 MHz for a 20 MHz channel)
Detector Mode:	Peak
Trace Mode:	Max Hold

2. When the trace is complete, capture the trace.
3. Find the peak value of the trace and place the analyser marker on this peak.
4. Use the 99 % bandwidth function of the spectrum analyser to measure the Occupied Channel Bandwidth of the UUT. This value shall be recorded.
5. Repeated steps 1 to 3 above in case of simultaneous transmissions in non-adjacent channels.
6. These measurements shall be performed only under normal operating conditions.
7. One channel out of the declared channels for each sub-band shall be tested.




Ant 1

Mode	Channel	Frequency (MHz)	99% bandwidth (MHz)	Result
802.11 a	CH36	5180	16.364	Pass
802.11 n HT 20	CH36	5180	17.581	Pass
802.11 n HT 40	CH38	5190	36.031	Pass
802.11 ac HT 20	CH36	5180	17.582	Pass
802.11 ac HT 40	CH38	5190	36.067	Pass
802.11 ac HT 80	CH42	5210	74.817	Pass


802.11 ac HT 20

CH36



802.11 n HT 20


CH36






802.11 n HT 40

CH38




802.11 ac HT 20

CH36






802.11 ac HT 40 CH38



802.11 ac HT 80 CH42




Note: Only the worst channel is reported for each modulation.

Ant 2

Mode	Channel	Frequency (MHz)	99% bandwidth (MHz)	Result
802.11 a	CH36	5180	16.366	Pass
802.11 n HT 20	CH36	5180	17.583	Pass
802.11 n HT 40	CH38	5190	36.045	Pass
802.11 ac HT 20	CH36	5180	17.584	Pass
802.11 ac HT 40	CH38	5190	36.081	Pass
802.11 ac HT 80	CH42	5210	74.770	Pass


802.11 ac HT 20

CH36



802.11 n HT 20

CH36




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.




802.11 n HT 40

CH38




802.11 ac HT 20

CH36






802.11 ac HT 40 CH38



802.11 ac HT 80 CH42



Note: Only the worst channel is reported for each modulation.



4.3. RF output power, Transmit Power Control (TPC) and power density

LIMIT

The limits below are applicable to the system as a whole and in any possible configuration. Includes smart antenna systems (devices with multiple transmit chains).

In case of multiple (adjacent or non-adjacent) channels within the same sub-band, the total RF output power of all channels in that sub-band shall not exceed the limits defined below.

In case of multiple, non-adjacent channels operating in separate sub-bands, the total RF output power in each of the sub-bands shall not exceed the limits defined below.

TPC is not required for channels whose nominal bandwidth falls completely within the band 5 150 MHz to 5 250 MHz.

For devices with TPC, the RF output power and the power density when configured to operate at the highest stated power level of the TPC range shall not exceed the levels given in table 1.

Devices are allowed to operate without TPC. See table 1 for the applicable limits in this case.

Table 1: Mean e.i.r.p. limits for RF output power and power density at the highest power level

Frequency range [MHz]	Mean e.i.r.p. limit [dBm]		Mean e.i.r.p. density limit [dBm/MHz]	
	with TPC	without TPC	with TPC	without TPC
5 150 to 5 350	23	20/23 (see note 1)	10	7/10 (see note 2)
5 470 to 5 725	30 (see note 3)	27 (see note 3)	17 (see note 3)	14 (see note 3)
NOTE 1: The applicable limit is 20 dBm, except for transmissions whose nominal bandwidth falls completely within the band 5 150 MHz to 5 250 MHz, in which case the applicable limit is 23 dBm.				
NOTE 2: The applicable limit is 7 dBm/MHz, except for transmissions whose nominal bandwidth falls completely within the band 5 150 MHz to 5 250 MHz, in which case the applicable limit is 10 dBm/MHz.				
NOTE 3: Slave devices without a Radar Interference Detection function shall comply with the limits for the band 5 250 MHz to 5 350 MHz.				

For devices using TPC, the RF output power during a transmission burst when configured to operate at the lowest stated power level of the TPC range shall not exceed the levels given in table 2.

For devices without TPC, the limits in table 2 do not apply.

Table 2: Mean e.i.r.p. limits for RF output power at the lowest power level of the TPC range

Frequency range	Mean e.i.r.p. [dBm]
5 250 MHz to 5 350 MHz	17
5 470 MHz to 5 725 MHz	24 (see note)
NOTE: Slave devices without a Radar Interference Detection function shall comply with the limits for the band 5 250 MHz to 5 350 MHz.	



4.3.1. RF output power at the highest power - PH

Test Procedure

1. The UUT shall be configured to operate at:
 - The highest stated transmitter output power level of the TPC range; or
 - The maximum transmitter output power level in case the equipment has no TPC feature.
2. For equipment with continuous transmission capability or for equipment operating (or with the capability to operate) with a constant duty cycle reference clause 5.4.4.2.1.1.2 ETSI EN 301 893 V2.1.1 (2017-05)
3. For equipment without continuous transmission capability and operating (or with the capability to operate) in only one sub-band reference clause 5.4.4.2.1.1.3 ETSI EN 301 893 V2.1.1 (2017-05)
4. For equipment without continuous transmission capability and having simultaneous transmissions in both sub-bands reference clause 5.4.4.2.1.1.4 ETSI EN 301 893 V2.1.1 (2017-05)
5. These measurements shall be performed under both normal and extreme test conditions.

**Test Results**

802.11a							
Test conditions		Channel/ Frequency	Ant 1	Ant 2	Mimo	Limit (dBm)	Result
Temperatur e (°C)	Voltage (V)		power (dBm)	power (dBm)	power (dBm)		
+25°C	5.0V	36/5180	10.47	10.76	/	23	Pass
-10°C	5.5V		10.97	11.11	/		Pass
	4.5V		10.27	10.52	/		Pass
+40°C	5.5V		11.55	11.07	/		Pass
	4.5V		11.36	10.61	/		Pass

802.11 n HT 20							
Test conditions		Channel/ Frequency	Ant 1	Ant 2	Mimo	Limit (dBm)	Result
Temperatur e (°C)	Voltage (V)		power (dBm)	power (dBm)	power (dBm)		
+25°C	5.0V	36/5180	9.45	9.84	12.66	23	Pass
-10°C	5.5V		9.23	8.67	11.97		Pass
	4.5V		9.70	9.02	12.38		Pass
+40°C	5.5V		8.72	9.21	11.98		Pass
	4.5V		8.67	10.25	12.54		Pass

802.11 n HT 40							
Test conditions		Channel/ Frequency	Ant 1	Ant 2	Mimo	Limit (dBm)	Result
Temperatur e (°C)	Voltage (V)		power (dBm)	power (dBm)	power (dBm)		
+25°C	5.0V	38/5190	7.20	7.44	10.33	23	Pass
-10°C	5.5V		8.04	7.42	10.75		Pass
	4.5V		6.93	6.62	9.79		Pass
+40°C	5.5V		6.64	5.88	9.29		Pass
	4.5V		7.10	7.20	10.16		Pass



802.11 ac HT 20							
Test conditions		Channel/ Frequency	Ant 1	Ant 2	Mimo	Limit (dBm)	Result
Temperatur e (°C)	Voltage (V)		power (dBm)	power (dBm)	power (dBm)		
+25°C	5.0V	36/5180	6.81	6.55	9.69	23	Pass
-10°C	5.5V		6.58	6.59	9.60		Pass
	4.5V		6.20	6.57	9.40		Pass
+40°C	5.5V		7.22	6.71	9.98		Pass
	4.5V		6.13	6.89	9.54		Pass

802.11 ac HT 40							
Test conditions		Channel/ Frequency	Ant 1	Ant 2	Mimo	Limit (dBm)	Result
Temperatur e (°C)	Voltage (V)		power (dBm)	power (dBm)	power (dBm)		
+25°C	5.0V	38/5190	6.01	5.55	8.80	23	Pass
-10°C	5.5V		7.63	6.65	10.18		Pass
	4.5V		5.75	5.84	8.81		Pass
+40°C	5.5V		5.52	5.25	8.40		Pass
	4.5V		6.93	6.25	9.61		Pass

802.11 ac HT 80							
Test conditions		Channel/ Frequency	Ant 1	Ant 2	Mimo	Limit (dBm)	Result
Temperatur e (°C)	Voltage (V)		power (dBm)	power (dBm)	power (dBm)		
+25°C	5.0V	42/5210	5.79	6.42	9.13	23	Pass
-10°C	5.5V		7.18	6.75	9.98		Pass
	4.5V		5.78	6.33	9.07		Pass
+40°C	5.5V		5.82	5.07	8.47		Pass
	4.5V		6.95	6.71	9.84		Pass



4.3.2. RF output power at the lowest power level of the TPC range - PL

Test Procedure

1. The UUT shall be configured to operate at the lowest stated transmitter output power level of the TPC range.
2. For equipment with continuous transmission capability or for equipment operating (or with the capability to operate) with a constant duty cycle (e.g. Frame Based equipment) reference clause 5.4.4.2.1.2.2 ETSI EN 301 893 V2.1.1 (2017-05)
3. For equipment without continuous transmission capability and operating (or with the capability to operate) in only one sub-band reference clause 5.4.4.2.1.2.3 ETSI EN 301 893 V2.1.1 (2017-05)
4. For equipment without continuous transmission capability and having simultaneous transmissions in both sub-bands reference clause 5.4.4.2.1.2.4 ETSI EN 301 893 V2.1.1 (2017-05)
5. These measurements shall be performed under both normal and extreme test conditions.
6. This test is only required for equipment with a TPC feature.

Test Results

This test item is not applicable for the EUT without TPC featur.



4.4. Power density

Test Procedure

1. The UUT shall be configured to operate at:
 - The highest stated transmitter output power level of the TPC range; or
 - The maximum transmitter output power level in case the equipment has no TPC feature.
2. For equipment with continuous transmission capability or for equipment operating (or with the capability to operate) with a constant duty cycle (e.g. Frame Based equipment) reference clause 5.4.4.2.1.3.2 ETSI EN 301 893 V2.1.1 (2017-05).
3. For equipment without continuous transmission capability and without the capability to transmit with a constant duty cycle reference clause 5.4.4.2.1.3.3 ETSI EN 301 893 V2.1.1 (2017-05).
4. These measurements shall only be performed at normal test conditions.

Test Results

Mode	Channel/ Frequency (MHz)	Ant 1	Ant 2	Mimo	Limit (dBm/MHz)	Result
		PSD (dBm/MHz)	PSD (dBm/MHz)	PSD (dBm/MHz)		
802.11a	36/5180	-0.99	1.84	/	10	Pass
802.11n HT 20	36/5180	-1.45	1.33	3.17	10	Pass
802.11n HT 40	38/5190	-3.90	-1.94	0.20	10	Pass
802.11ac HT 20	36/5180	-0.74	1.41	3.48	10	Pass
802.11ac HT 40	38/5190	-3.80	-1.78	0.34	10	Pass
802.11ac HT 80	42/5210	-6.22	-5.08	-2.60	10	Pass

Note: Only the worst channel is reported for each modulation.



The test plots as follow:
Ant 1




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

HUAKE Testing Lab TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




802.11n HT 20



CH36




802.11n HT 40



CH38




802.11ac HT 20



CH36




802.11ac HT 40



CH38



802.11ac HT 80





CH42



Ant 2


802.11a



CH36




802.11n HT 20



CH36





802.11n HT 40



CH38




802.11ac HT 20



CH36




802.11ac HT 40



CH38



802.11ac HT 80



CH42



4.5. Transmitter unwanted emissions

4.5.1. Transmitter unwanted emissions outside the 5 GHz RLAN bands

Limit

The level of unwanted emission shall not exceed the limits given in table 3.

Table 3: Transmitter unwanted emission limits outside the 5 GHz RLAN bands


Frequency range	Maximum power	Bandwidth
30 MHz to 47 MHz	-36 dBm	100 kHz
47 MHz to 74 MHz	-54 dBm	100 kHz
74 MHz to 87,5 MHz	-36 dBm	100 kHz
87,5 MHz to 118 MHz	-54 dBm	100 kHz
118 MHz to 174 MHz	-36 dBm	100 kHz
174 MHz to 230 MHz	-54 dBm	100 kHz
230 MHz to 470 MHz	-36 dBm	100 kHz
470 MHz to 862 MHz	-54 dBm	100 kHz
862 MHz to 1 GHz	-36 dBm	100 kHz
1 GHz to 5,15 GHz	-30 dBm	1 MHz
5,35 GHz to 5,47 GHz	-30 dBm	1 MHz
5,725 GHz to 26 GHz	-30 dBm	1 MHz

Test Procedure

1. The measurement procedure follows ETSI EN 301 893 (V2.1.1) Sub-clause 5.4.5.2.2
2. The measurement shall only be performed at normal test conditions.
One channel out of the declared channels for each sub-band shall be tested.

Test Configuration

Effective Radiated Power measurement (30 MHz to 26 GHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

**TEST RESULTS**

Remark: We tested at 802.11a/802.11n HT20/802.11n HT40/802.11ac HT20/802.11ac HT40/802.11ac HT80 mode at the antenna single transmitting mode and the Mimo mode, and recorded the worst case 802.11n HT 20 mode at the Mimo mode. 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.

802.11n HT 20, CH 36, Horizontal/Vertical

Fre. (MHz)	ANT. Pol.	Result (dBm)	Limit	Margin	Conclusion
Below 1GHz:					
229.85	V	-75.10	-54	-21.10	PASS
245.80	V	-77.09	-54	-23.09	PASS
338.94	V	-77.95	-36	-41.95	PASS
444.73	V	-78.61	-36	-42.61	PASS
537.91	V	-74.97	-54	-20.97	PASS
836.12	V	-78.83	-36	-42.83	PASS
195.17	H	-73.33	-54	-19.33	PASS
248.94	H	-79.40	-36	-43.40	PASS
346.65	H	-71.38	-36	-35.38	PASS
435.48	H	-76.15	-36	-40.15	PASS
612.06	H	-72.66	-54	-18.66	PASS
860.53	H	-77.82	-36	-41.82	PASS
Note: 1. Cable loss and antenna gain was combined in the calculated result. 2. Other point of the measurements are below 20dB from the limit.					




Fre. (MHz)	ANT. Pol.	Result (dBm)	Limit	Margin	Conclusion
Above 1GHz:					
1932.33	V	-53.71	-30	-23.71	PASS
2524.67	V	-55.51	-30	-25.51	PASS
3581.73	V	-56.68	-30	-26.68	PASS
4301.65	V	-59.24	-30	-29.24	PASS
5551.76	V	-53.06	-30	-23.06	PASS
5968.61	V	-55.76	-30	-25.76	PASS
2207.09	H	-54.02	-30	-24.02	PASS
2520.53	H	-58.38	-30	-28.38	PASS
3009.38	H	-51.57	-30	-21.57	PASS
3959.82	H	-53.63	-30	-23.63	PASS
4951.43	H	-51.24	-30	-21.24	PASS
6769.48	H	-50.83	-30	-20.83	PASS
Note: 1.Cable loss and antenna gain was combined in the calculated result. 2. Other point of the measurements are below 20dB from the limit.					



4.5.2. Transmitter unwanted emissions within the 5 GHz RLAN bands

LIMIT



NOTE: dBc is the spectral density relative to the maximum spectral power density of the transmitted signal.

Figure 1: Transmit spectral power mask

Test Procedure

1. The measurement procedure follows ETSI EN 301 893 (V2.1.1) Sub-clause 4.6.2.1.
2. The measurement shall only be performed at normal test conditions.

Test Result


The test plots as follow:



Ant 1


802.11a HT 20

CH36



802.11n HT 20


CH36






802.11n HT 40

CH38



802.11ac HT 20



CH36






802.11ac HT 40

CH38



802.11ac HT 80

CH42





Ant 2

802.11a HT 20

CH36



802.11n HT 20

CH36



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.



HUAKE Testing Lab TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




802.11n HT 40

CH38



802.11ac HT 20


CH36






802.11ac HT 40

CH38



802.11ac HT 80

CH42





4.6. Receiver spurious emissions

The spurious emissions of the receiver shall not exceed the limits given in table 4.

Table 4: Spurious radiated emission limits


Frequency range	Maximum power	Measurement bandwidth
30 MHz to 1 GHz	-57 dBm	100 kHz
1 GHz to 26 GHz	-47 dBm	1 MHz

Test Procedure

1. The measurement procedure follows ETSI EN 301 893 (V2.1.1) Sub-clause 5.4.7.2.2
2. The measurement shall only be performed at normal test conditions.
3. One channel out of the declared channels for each sub-band shall be tested.

Test Configuration

Effective Radiated Power measurement (30 MHz to 26 GHz)



**TEST RESULTS**

Note: We tested at 802.11a/802.11n HT20/802.11n HT40/802.11ac HT20/802.11ac HT40/802.11ac HT80 mode at the antenna single receiver mode and the Mimo mode, and recorded the worst case 802.11n HT 20 mode at the Mimo mode. 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.

802.11n HT 20, CH 36, Horizontal/Vertical

Fre. (MHz)	ANT. Pol.	Result (dBm)	Limit	Margin	Conclusion
Below 1GHz:					
213.48	V	-73.90	-57	-16.90	PASS
248.56	V	-76.21	-57	-19.21	PASS
342.91	V	-81.57	-57	-24.57	PASS
463.04	V	-72.87	-57	-15.87	PASS
543.58	V	-79.76	-57	-22.76	PASS
846.09	V	-81.50	-57	-24.50	PASS
261.04	H	-79.19	-57	-22.19	PASS
288.14	H	-76.80	-57	-19.80	PASS
338.30	H	-75.09	-57	-18.09	PASS
454.16	H	-78.51	-57	-21.51	PASS
633.18	H	-75.94	-57	-18.94	PASS
858.47	H	-71.55	-57	-14.55	PASS
Note: 1. Cable loss and antenna gain was combined in the calculated result. 2. Other point of the measurements are below 20dB from the limit.					



Fre. (MHz)	ANT. Pol.	Result (dBm)	Limit	Margin	Conclusion
Below 1GHz:					
2292.42	V	-76.38	-47	-29.38	PASS
2512.70	V	-75.38	-47	-28.38	PASS
3536.49	V	-73.10	-47	-26.10	PASS
4282.34	V	-75.86	-47	-28.86	PASS
5359.78	V	-74.77	-47	-27.77	PASS
5996.96	V	-78.05	-47	-31.05	PASS
2264.45	H	-71.46	-47	-24.46	PASS
2285.50	H	-78.57	-47	-31.57	PASS
3278.84	H	-76.21	-47	-29.21	PASS
3909.14	H	-75.21	-47	-28.21	PASS
5040.74	H	-71.94	-47	-24.94	PASS
6712.86	H	-79.94	-47	-32.94	PASS
Note: 1.Cable loss and antenna gain was combined in the calculated result. 2. Other point of the measurements are below 20dB from the limit.					



4.7. Dynamic Frequency Selection (DFS)

DFS parameters

Table D.1: DFS requirement values

Parameter	Value
Channel Availability Check Time	60 s (see note 1)
Minimum Off-Channel CAC Time	6 minutes (see note 2)
Maximum Off-Channel CAC Time	4 hours (see note 2)
Channel Move Time	10 s
Channel Closing Transmission Time	1 s
Non-Occupancy Period	30 minutes
NOTE 1: For channels whose nominal bandwidth falls completely or partly within the band 5 600 MHz to 5 650 MHz, the <i>Channel Availability Check Time</i> shall be 10 minutes.	
NOTE 2: For channels whose nominal bandwidth falls completely or partly within the band 5 600 MHz to 5 650 MHz, the <i>Off-Channel CAC Time</i> shall be within the range 1 to 24 hours.	

Table D.2: Interference threshold values

e.i.r.p. Spectral Density dBm/MHz	Value (see notes 1 and 2)
10	-62 dBm
NOTE 1: This is the level at the input of the receiver of an RLAN device with a maximum e.i.r.p. density of 10 dBm/MHz and assuming a 0 dBi receive antenna. For devices employing different e.i.r.p. spectral density and/or a different receive antenna gain G (dBi) the DFS threshold level at the receiver input follows the following relationship: DFS Detection Threshold (dBm) = -62 + 10 · e.i.r.p. Spectral Density (dBm/MHz) + G (dBi), however the DFS threshold level shall not be lower than -64 dBm assuming a 0 dBi receive antenna gain.	
NOTE 2: Slave devices with a maximum e.i.r.p. of less than 23 dBm do not have to implement radar detection.	

Table D.3: Parameters of the reference DFS test signal

Pulse width W [μs]	Pulse repetition frequency PRF [PPS]	Pulses per burst [PPB]
1	700	18




Table D.4: Parameters of radar test signals

Radar test signal # (see notes 1 to 3)	Pulse width W [μ s]		Pulse repetition frequency PRF (PPS)		Number of different PRFs	Pulses per burst for each PRF (PPB) (see note 5)
	Min	Max	Min	Max		
1	0,5	5	200	1 000	1	10 (see note 6)
2	0,5	15	200	1 600	1	15 (see note 6)
3	0,5	15	2 300	4 000	1	25
4	20	30	2 000	4 000	1	20
5	0,5	2	300	400	2/3	10 (see note 6)
6	0,5	2	400	1 200	2/3	15 (see note 6)

NOTE 1: Radar test signals 1 to 4 are constant PRF based signals. See figure D.1. These radar test signals are intended to simulate also radars using a packet based Staggered PRF. See figure D.2.

NOTE 2: Radar test signal 4 is a modulated radar test signal. The modulation to be used is a chirp modulation with a $\pm 2,5$ MHz frequency deviation which is described below.



NOTE 3: Radar test signals 5 and 6 are single pulse based Staggered PRF radar test signals using 2 or 3 different PRF values. For radar test signal 5, the difference between the PRF values chosen shall be between 20 PPS and 50 PPS. For radar test signal 6, the difference between the PRF values chosen shall be between 80 PPS and 400 PPS. See figure D.3.

NOTE 4: Apart for the Off-Channel CAC testing, the radar test signals above shall only contain a single burst of pulses. See figures D.1, D.3 and D.4. For the Off-Channel CAC testing, repetitive bursts shall be used for the total duration of the test. See figures D.2 and D.5. See also clauses 4.7.2.2, 5.3.8.2.1.3.1 and 5.3.8.2.1.3.2.

NOTE 5: The total number of pulses in a burst is equal to the number of pulses for a single PRF multiplied by the number of different PRFs used.

NOTE 6: For the CAC and Off-Channel CAC requirements, the minimum number of pulses (for each PRF) for any of the radar test signals to be detected in the band 5 600 MHz to 5 650 MHz shall be 18.

Table D.5: Detection probability

Parameter	Detection Probability (P_d)	
	Channels whose nominal bandwidth falls partly or completely within the 5 600 MHz to 5 650 MHz band	Other channels
CAC, Off-Channel CAC	99,99 %	60 %
In-Service Monitoring	60 %	60 %
NOTE:	P_d gives the probability of detection per simulated radar burst and represents a minimum level of detection performance under defined conditions. Therefore P_d does not represent the overall detection probability for any particular radar under real life conditions.	



Test set-ups

Set-up A

Set-up A is a set-up whereby the UUT is an RLAN device operating in master mode. Radar test signals are injected into the UUT. This set-up also contains an RLAN device operating in slave mode which is associated with the UUT.




Figure 4: Set-up A

Set-up B

Set-up B is a set-up whereby the UUT is an RLAN device operating in slave mode, with or without Radar Interference Detection function. This set-up also contains an RLAN device operating in master mode. The radar test signals are injected into the master device. The UUT (slave device) is associated with the master device.




Figure 5: Set-up B

Set-up C

The UUT is an RLAN device operating in slave mode with Radar Interference Detection function. Radar test signals are injected into the slave device. This set-up also contains an RLAN device operating in master mode. The UUT (slave device) is associated with the master device.




Figure 6: Set-up C

**DFS technical requirements specifications**

Follow table lists the DFS related technical requirements and their applicability for every operational mode. If the RLAN device is capable of operating in more than one operational mode then every operating mode shall be assessed separately.

Applicability of DFS requirements

Requirement	DFS Operational mode		
	Master	Slave without radar detection	Slave with radar detection (see table D.2, note 2)
Channel Availability Check	✓	Not required	✓ (see note 2)
Off-Channel CAC (see note 1)	✓	Not required	✓ (see note 2)
In-Service Monitoring	✓	Not required	✓
Channel Shutdown	✓	✓	✓
Non-Occupancy Period	✓	Not required	✓
Uniform Spreading	✓	Not required	Not required
NOTE 1: Where implemented by the manufacturer.			
NOTE 2: A slave with radar detection is not required to perform a CAC or Off-Channel CAC at initial use of the channel but only after the slave has detected a radar signal on the Operating Channel by In-Service Monitoring.			

TEST RESULTS

Testing is not required for nominal channel bandwidths that fall completely within the frequency range 5 150 MHz to 5 250 MHz. So this test item is not applicable for the EUT.



4.8. Adaptivity


Requirements and limits

When interference signal detected by relevant channel access mechanism UUT used. The UUT should stops transmissions on the current operating channel, apart from Short Control Signaling Transmissions with a maximum duty cycle of 5 % within an observation period of 50 ms,


Test Procedure

1. The measurement procedure follows the clause 5.3.9.2.1 of the ETSI EN 301 893 V2.1.1 (2017-05).
2. The inference signal used shall be a band limited noise signal with a 100 % duty cycle.
3. Testing shall be performed at one channel out of the declared channels for each sub-band and the highest nominal channel bandwidth.

Test Configuration



Adaptivity Test schematic graphic





Test Step 2 :We add the Additive white Gaussian noise (AWGN) as interference Signal

Test step 3 and Test step 3_2nd : We Repeat Test Step 2 and Test Step 2_2nd ,but We add the OFDM test signal as interference Signal

Test step 4 and Test step 4_2nd : We Repeat Test Step 2 and Test Step 2_2nd ,but We add LTE test signal as interference Signal

TEST RESULTS

Ant 1
Adaptivity 1

Test Mode	Test Channel	Priority Class	COT Num[n]	Max.COT [ms]	Limit [ms]	Min. Idel Time [ms]	Limit [ms]
802.11a	5180	2	868	1.144	<=6	0.046	>0.027
802.11n HT 20	5180	2	932	0.251	<=6	0.042	>0.027
802.11n HT 40	5190	2	925	0.239	<=6	0.044	>0.027
802.11ac HT 20	5180	2	847	1.155	<=6	0.039	>0.027
802.11ac HT 40	5190	2	943	0.175	<=6	0.041	>0.027
802.11ac HT 80	5210	2	917	0.191	<=6	0.052	>0.027



Test Mode	Test Channel	Interference signal Type	Add interference signal Time[ms]	Interference signal Level [dBm/MHz]	Max.Short Control number[n]	Limit [n]	Max.Short Control Time [ms]	Limit [ms]
802.11a	5180	LTE	2000	-75	5	<=50	0.48	<2.5
802.11a	5180	OFDM	2000	-75	5	<=50	0.18	<2.5
802.11a	5180	AWGN	2000	-75	5	<=50	0.18	<2.5
802.11n HT 20	5180	LTE	2000	-75	5	<=50	0.05	<2.5
802.11n HT 20	5180	OFDM	2000	-75	5	<=50	0.78	<2.5
802.11n HT 20	5180	AWGN	2000	-75	5	<=50	0.40	<2.5
802.11n HT 40	5190	LTE	2000	-75	5	<=50	0.25	<2.5
802.11n HT 40	5190	OFDM	2000	-75	5	<=50	0.57	<2.5
802.11n HT 40	5190	AWGN	2000	-75	5	<=50	0.60	<2.5
802.11ac HT 20	5180	LTE	2000	-75	5	<=50	0.44	<2.5
802.11ac HT 20	5180	OFDM	2000	-75	5	<=50	0.48	<2.5
802.11ac HT 20	5180	AWGN	2000	-75	5	<=50	1.91	<2.5
802.11ac HT 40	5190	LTE	2000	-75	5	<=50	0.44	<2.5
802.11ac HT 40	5190	OFDM	2000	-75	5	<=50	0.66	<2.5
802.11n HT 40	5190	AWGN	2000	-75	5	<=50	2.13	<2.5
802.11ac HT 80	5210	LTE	2000	-75	5	<=50	0.39	<2.5
802.11ac HT 80	5210	OFDM	2000	-75	5	<=50	0.20	<2.5
802.11ac HT 80	5210	AWGN	2000	-75	5	<=50	0.77	<2.5

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.



Ant 2
Adaptivity 1

Test Mode	Test Channel	Priority Class	COT Num[n]	Max.COT [ms]	Limit [ms]	Min. Idel Time [ms]	Limit [ms]
802.11a	5180	2	868	1.142	<=6	0.046	>0.027
802.11n HT 20	5180	2	932	0.246	<=6	0.046	>0.027
802.11n HT 40	5190	2	925	0.234	<=6	0.045	>0.027
802.11ac HT 20	5180	2	847	1.152	<=6	0.034	>0.027
802.11ac HT 40	5190	2	943	0.173	<=6	0.045	>0.027
802.11ac HT 80	5210	2	917	0.192	<=6	0.051	>0.027

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

HUAKE Testing Lab TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



Test Mode	Test Channel	Interference signal Type	Add interference signal Time[ms]	Interference signal Level [dBm/MHz]	Max.Short Control number[n]	Limit [n]	Max.Short Control Time [ms]	Limit [ms]
802.11a	5180	LTE	2000	-75	5	<=50	0.73	<2.5
802.11a	5180	OFDM	2000	-75	5	<=50	0.67	<2.5
802.11a	5180	AWGN	2000	-75	5	<=50	0.24	<2.5
802.11n HT 20	5180	LTE	2000	-75	5	<=50	0.23	<2.5
802.11n HT 20	5180	OFDM	2000	-75	5	<=50	0.42	<2.5
802.11n HT 20	5180	AWGN	2000	-75	5	<=50	0.63	<2.5
802.11n HT 40	5190	LTE	2000	-75	5	<=50	0.22	<2.5
802.11n HT 40	5190	OFDM	2000	-75	5	<=50	0.05	<2.5
802.11n HT 40	5190	AWGN	2000	-75	5	<=50	0.57	<2.5
802.11ac HT 20	5180	LTE	2000	-75	5	<=50	0.76	<2.5
802.11ac HT 20	5180	OFDM	2000	-75	5	<=50	0.76	<2.5
802.11ac HT 20	5180	AWGN	2000	-75	5	<=50	2.12	<2.5
802.11ac HT 40	5190	LTE	2000	-75	5	<=50	0.29	<2.5
802.11ac HT 40	5190	OFDM	2000	-75	5	<=50	0.15	<2.5
802.11n HT 40	5190	AWGN	2000	-75	5	<=50	2.31	<2.5
802.11ac HT 80	5210	LTE	2000	-75	5	<=50	0.13	<2.5
802.11ac HT 80	5210	OFDM	2000	-75	5	<=50	0.53	<2.5
802.11ac HT 80	5210	AWGN	2000	-75	5	<=50	0.89	<2.5

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.



4.9. Receiver Blocking

Limits


ETSI EN 301 893 Sub-4.2.8.4

While maintaining the minimum performance criteria as defined in clause 4.2.8.3, the blocking levels at specified frequency offsets shall be equal to or greater than the limits defined in table 9.

Table 9: Receiver Blocking parameters

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 2)		Type of blocking signal
		Master or Slave with radar detection (see table D.2, note 2)	Slave without radar detection (see table D.2, note 2)	
P _{min} + 6 dB	5 100	-53	-59	Continuous Wave
P _{min} + 6 dB	4 900 5 000 5 975	-47	-53	Continuous Wave
NOTE 1: P _{min} is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined clause 4.2.8.3 in the absence of any blocking signal.				
NOTE 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the same levels should be used at the antenna connector irrespective of antenna gain.				

TEST CONFIGURATION:



TEST PROCEDURE

Please refer to ETSI EN 301 893 Sub-clause 4.2.8.2 for the measurement method..

TEST RESULTS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.



For ANT 1

For 11a

5180MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-53	10%	5%	PASS
	4900	-47	10%	5%	PASS
	5000	-47	10%	6%	PASS
	5975	-47	10%	4%	PASS

For 11n HT20

5180MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-53	10%	4%	PASS
	4900	-47	10%	5%	PASS
	5000	-47	10%	5%	PASS
	5975	-47	10%	6%	PASS

For 11n HT40

5180MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-53	10%	5%	PASS
	4900	-47	10%	6%	PASS
	5000	-47	10%	4%	PASS
	5975	-47	10%	5%	PASS



For 11ac HT20

5180MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-53	10%	5%	PASS
	4900	-47	10%	5%	PASS
	5000	-47	10%	6%	PASS
	5975	-47	10%	4%	PASS

For 11ac HT40

5190MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-53	10%	6%	PASS
	4900	-47	10%	4%	PASS
	5000	-47	10%	6%	PASS
	5975	-47	10%	4%	PASS

For 11ac HT80

5210MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-53	10%	5%	PASS
	4900	-47	10%	6%	PASS
	5000	-47	10%	4%	PASS
	5975	-47	10%	6%	PASS



For ANT 2

For 11a

5180MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-53	10%	6%	PASS
	4900	-47	10%	5%	PASS
	5000	-47	10%	5%	PASS
	5975	-47	10%	5%	PASS

For 11n HT20

5180MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-53	10%	5%	PASS
	4900	-47	10%	5%	PASS
	5000	-47	10%	4%	PASS
	5975	-47	10%	4%	PASS

For 11n HT40

5180MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-53	10%	5%	PASS
	4900	-47	10%	5%	PASS
	5000	-47	10%	4%	PASS
	5975	-47	10%	6%	PASS



For 11ac HT20

5180MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-53	10%	4%	PASS
	4900	-47	10%	6%	PASS
	5000	-47	10%	5%	PASS
	5975	-47	10%	5%	PASS

For 11ac HT40

5190MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-53	10%	4%	PASS
	4900	-47	10%	5%	PASS
	5000	-47	10%	6%	PASS
	5975	-47	10%	5%	PASS

For 11ac HT80

5210MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-53	10%	5%	PASS
	4900	-47	10%	5%	PASS
	5000	-47	10%	4%	PASS
	5975	-47	10%	4%	PASS



4.10. User Access Restrictions

Requirement

The equipment shall be so constructed that settings (hardware and/or software) related to DFS shall not be accessible to the user if changing those settings result in the equipment no longer being compliant with the DFS requirements in EN301893 (clause 4.7) The above requirement includes the prevention of indirect access to any setting that impacts DFS.

Result

The EUT do not use the DFS Band and The customers will not obtain the information to set hardware and/ software related to DFS, if the product is on sales. So The EUT meets this requirement.



4.11. Geo-location capability

Requirement

Geo-location capability is a feature of the RLAN device to determine its geographical location with the purpose to configure itself according to the regulatory requirements applicable at the geographical location where it operates. The geo-location capability may be present in the equipment or in an external device (temporary) associated with the equipment operating at the same geographical location during the initial power up of the equipment. The geographical location may also be available in equipment already installed and operating at the same geographical location.

The geographical location determined by the equipment as defined in the above shall not be accessible to the user.

Result

This requirement only applies to equipment with geo-location capability, and the EUT do not support this function. So this requirement is not applicable for the EUT.



5. Test Setup Photos of the EUT



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

HUAKE Testing Lab TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



6. External and Internal Photos of the EUT






The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

HUAKE Testing Lab TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

HUAKE Testing Lab TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com



1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

HUAKE Testing Lab TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China






The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

HUAKE Testing Lab TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com


1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

HUAKE Testing Lab TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com



1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

HUAKE Testing Lab TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



.....End of Report.....