

Number: **JW-360-12**

Name: **0-12V30A**

Spec: **215mm\*115mm\*50mm**

Memo: **24pieces/carton**

Class: **12V single output**

AC input selectable by switch

Protection: Overload /Over voltage/Over temperature/Short circuit

LED power on indication

100% full load burn-in test

Built-in EMI filter

1 year warranty

MTBF>50,000 hours

AC Input voltage range.....AC88V-132V/AC180-264V (selected by switch)

Input frequency.....47~63Hz

AC inrush current.....5A/115V, 30A/230V (cold start)

DC voltage adjustment range.....0-12V

Output rated current.....30A

Output current range.....0~30A

Rise time.....50ms@full load (typical)

Hold up time.....20ms@full load (typical)

Operating temp. & humidity .....-20°C ~ +55°C, 20% ~ 93%RH (non condensing)

Storage temp. & humidity .....-40°C ~ +85°C, 10% ~ 95%RH (non condensing)

Cooling .....fan

Safety standards.....GB4943, UL60950-1, EN60950-1

EMC standards.....GB9254, EN55022 CLASS A

Withstand voltage.....I/P-O/P: 1.5KVAC/IMIN

I/P-FG: 1.5KVAC/IMIN

O/P-FG: 0.5KVAC /1MIN