



# MPE TEST REPORT

**Product :** IP Camera

**Trade Mark :** Sricam

**Model Name :** SP012

**Serial Model :** SP005, SP006, SP007, SP008, SP009, SP009B,  
SP009C, SP010, SP011, SP013, SP014, SP015,  
SP016, SP017, SP018, SP019, SP020, SP023,  
NVS001, NVS002.

**Report No. :** SER171225622001E

## Prepared for

Shenzhen Sricctv Technology Co., Ltd  
The 4th Floor of Building46, 5th Industrial Park of Huaide Cuigang,  
Fuyong Street, Bao' an, Shenzhen, China

## Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street  
Bao'an District, Shenzhen 518126 P.R. China  
Tel.: +86-755-6115 9388 Fax.: +86-755-6115 6599  
Website: <http://www.ntek.org.cn>



**TEST RESULT CERTIFICATION**

**Applicant's name** ..... : Shenzhen Sricctv Technology Co., Ltd  
**Address** ..... : The 4th Floor of Building46, 5th Industrial Park of Huaide  
Cuigang, Fuyong Street, Bao'an, Shenzhen, China

**Manufacturer's Name** ..... : Shenzhen Sricctv Technology Co., Ltd  
**Address** ..... : The 4th Floor of Building46, 5th Industrial Park of Huaide  
Cuigang, Fuyong Street, Bao'an, Shenzhen, China

**Product description**

**Product name** ..... : IP Camera

**Trademark** ..... : Sricam

**Model and/or type reference** : SP012

**Serial Model** : ..... : SP005, SP006, SP007, SP008, SP009, SP009B, SP009C,  
SP010, SP011, SP013, SP014, SP015, SP016, SP017, SP018,  
SP019, SP020, SP023, NVS001, NVS002.

**Rating(s)** ..... : DC 5V from Adapter

**Standards** ..... : Radiocommunications (Electromagnetic Radiation — Human  
Exposure) Standard 2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the C-tick requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

**Date of Test** .....

**Date (s) of performance of tests** ..... : 26 Dec. 2017 ~09 Mar. 2018


**Date of Issue** ..... : 09 Mar. 2018

**Test Result** ..... : **Pass**

**Testing Engineer** : Lake Xie  
(Lake Xie)

**Technical Manager** : Jason Chen  
(Jason Chen)

**Authorized Signatory** : Sam Chen  
(Sam Chen)





**Table of Contents****Page**

1 . General Information	4
1.1 General Description Of EUT	4
2 .EN 62311 REQUIREMENT	6
2.1 GENERAL INFORMATION	6
2.2 LIMIT	6
2.3 Limit calculations for radiated electric field strength measurement	9
3 .Result	10



## 1. General Information

### 1.1 General Description Of EUT

Equipment	IP Camera	
Trade Mark	Sricam	
Model Name.	SP012	
Serial Model	SP005, SP006, SP007, SP008, SP009, SP009B, SP009C, SP010, SP011, SP013, SP014, SP015, SP016, SP017, SP018, SP019, SP020, SP023, NVS001, NVS002.	
Model Difference	All the model are the same circuit and RF module, except the appearance.	
Product Description	The EUT is IP Camera	
	Operation Frequency:	802.11b/g/n(20MHz): 2412~2472MHz 802.11n(40MHz):2422~2462MHz
	Modulation Type:	IEEE 802.11b : DSSS (DBPSK, DQPSK, CCK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
	Number Of Channel	40CH
	Antenna Designation:	External Antenna
	Antenna Gain(Peak)	2dBi
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an IP Camera. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Refer to below	
Adapter	Model:KA1503-0502000AUS Input: 100-240V~50/60Hz 0.35A Output: 5V---2000mA	
Battery	N/A	
Power Rating	DC 5V from Adapter AC 100-240V, 50/60Hz	
Hardware Version	N/A	
Software Version	N/A	

#### Note

- 1 For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2

Channel	Frequency (MHz)
00	2402
01	2404
.....	.....
.....	.....
.....	...
.....	.....
38	2478
39	2480



## 2.EN 62311 REQUIREMENT

### 2.1 GENERAL INFORMATION

The essential requirements of Radiocommunications (Electromagnetic Radiation — Human Exposure) Standard 2014 in the article 12,

Assessment methods for performance standards: aware user devices and non-aware user devices more than 20cm from the human body

(1) This section applies to an aware user device or a non-aware user device to which this Standard applies that:

- (a) is designed to be used, or held, more than 20cm from the human body; and
- (b) transmits in the frequency band 300kHz to 100GHz (inclusive).

(2) The RF field produced by an aware user device or a non-aware user device, at the position of the user with the device operated at the normal position of use, must be assessed in accordance with the requirements in AS 2772.2.

(3) An aware user device is taken to meet the standard for performance of subsection 9 (1) if the RF field assessed under subsection (2) is less than the relevant reference levels for occupational exposure.

(4) A non-aware user device is taken to meet the standard for performance of subsection 9 (2) if the RF field assessed is less than the relevant reference levels for general public exposure.

### 2.2 LIMIT



### Basic Restrictions Reference levels

Council Recommendation 99/519/EC Annex II

Basic restrictions for electric, magnetic and electromagnetic fields (0Hz to 300GHz)

Frequency range	Magnetic flux density (mT)	Current density (Ma/m2) (rms)	Whole body average SAR (W/kg)	Localised SAR (head and trunk) (W/kg)	Localised SAR (limbs) (W/kg)	Power density, S (W/m2 )
0Hz	40	-	-	-	-	-
>0-1Hz	-	8	-	-	-	-
1-4Hz	-	8/f	-	-	-	-
4-1000Hz	-	2	-	-	-	-
1000Hz-100kHz	-	f/500	-	-	-	-
100kHz-10MHz	-	f/500	0.08	2	4	-
10MHz-10GHz	-	-	0.08	2	4	-
10-300GHz	-	-	-	-	-	10

Note:

(1)f is the frequency in Hz.

(2)The basic restriction on the current density is intended to protect against acute exposure effects on central nervous system tissues in the head and trunk of the body and includes a safety factor. The basic restrictions for ELF fields are based on established adverse effects on the central nervous system. Such acute effects are essentially instantaneous and there is no scientific justification to modify the basic restrictions for exposure of short duration. However, since the basic restriction refers to adverse effects on the central nervous system, this basic restriction may permit higher current densities in body tissues other than the central nervous system under the same exposure conditions.

(3)Because of electrical inhomogeneity of the body, current densities should be averaged over a cross section of 1cm<sup>2</sup> perpendicular to the current direction.

(4)For frequencies up to 100 kHz, peak current density values can be obtained by multiplying the rms value by  $\sqrt{2}$ (=1.414). For pulses of duration tp the equivalent frequency to apply in the basic restrictions should be calculated as=1/(2tp)

(5)For frequencies up to 100kHz and for pulsed magnetic fields, the maximum current density associated with the pulses can be calculated from the rise/fall times and the maximum rate of change of magnetic flux density. The induced current density can then be compared with the appropriate basic restriction.

(6)All SAR values are to be averaged over any six-minute period.



(7) Localised SAR averaging mass is any 10g of contiguous tissue; the maximum SAR so obtained should be the value used for the estimation of exposure. These 10g of tissue are intended to be a mass of contiguous tissue with nearly homogeneous electrical properties. In specifying a contiguous mass of tissue, it is recognised that this concept can be used in computational dosimetry but may present difficulties for direct physical measurements. A simple geometry such as cubic tissue mass can be used provided that the calculated dosimetric quantities have conservation values relative to the exposure guidelines.

(8) For pulses of duration  $t_p$  the equivalent frequency to apply in the basic restrictions should be calculated as  $\omega = 1/(2t_p)$ . Additionally, for pulsed exposures, in the frequency range 0,3 to 10GHz and for localised exposure of the head, in order to limit and avoid auditory effects caused by thermoelastic expansion, an additional basic restriction is recommended. This is that SA should not exceed 2mJ kg<sup>-1</sup> averaged over 10g of tissue.

### Reference Levels

Council Recommendation 99/519/EC Annex III

Reference levels for electric, magnetic and electromagnetic fields (0Hz to 300GHz)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density Seq (W/m <sup>2</sup> )
0-1Hz	-	$3,2 \times 10^4$	$4 \times 10^4$	-
1-8Hz	1000	$3,2 \times 10^4 / f^2$	$4 \times 10^4 / f^2$	-
8-25Hz	1000	$4000/f$	$5000/f$	-
0.025Hz-0,8kHz	$250/f$	$4/f$	$5/f_{6,25}$	-
0,8-3kHz	$250/f$	5	6,25	-
3-150kHz	87	5	6,25	-
0,15-1MHz	87	$0.73/f$	$0.92/f$	-
1-10MHz	$87/f^{1/2}$	$0.73/f$	$0.92/f$	-
10-400MHz	28	0.073	0.092	2
400-2000MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300GHz	61	0,16	0,20	10

Note:

(1) As indicated in the frequency range column.

(2) For frequencies between 100kHz and 10GHz, Seq, E2, H2 and B2 are to be averaged over any six-minute period.

(3) For frequencies exceeding 10GHz, Seq, E2, H2 and B2 are to be averaged over any 68/1.05-minute period (.in GHz).

(4) No E-field value is provided for frequencies <1Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 20kV/m. Spark discharges causing stress or annoyance should be avoided.



### 2.3 Limit calculations for radiated electric field strength measurement

For the calculation of the limits, the near field proportionality factor  $1/d^3$  has been used. For ten times the distance, the level is decreased by the cubical, giving 60 dB.

Frequency range	Limit V/m @0.3m	Limit V/m @3m	Limit (add.span)
30MHz-400MHz	28V/m(149dBuV/m)	89dBuV/m	69 dBuV/m
400MHz-2GHz	27.5V/m-61.5V/m (149dBuV/m-155dBuV/m)	89dBuV/m	69dBuV/m
		95dBuV/m	75dBuV/m
2GHz-300GHz	61V/m(155dBuV/m)	95dBuV/m	75dBuV/m

To deal with reflexions, other effects due to the measurement in 3 m distance and to deal with a measurement uncertainty of at least 5 dB, an additional span of 20 dB has been added.

For additional three times the distance, the level is decreased by additional 30 dB.

Frequency range	Limit V/m @0.1m	Limit V/m @3m	Limit (add.span)
30MHz-400MHz	28V/m(149dBuV/m)	59dBuV/m	39 dBuV/m
400MHz-2GHz	27.5V/m-61.5V/m (149dBuV/m-155dBuV/m)	59dBuV/m	39dBuV/m
		65dBuV/m	45dBuV/m
2GHz-300GHz	61V/m(155dBuV/m)	65dBuV/m	45dBuV/m

To deal with reflexions, other effects due to the measurement in 3 m distance and to deal with a measurement uncertainty of at least 5 dB, an additional span of 20 dB has been added.

Limits for radiated field according to EN 55022 / CISPR 22 for a class B appliance:

Frequency range	Limit dBuV/m @3m Peak	Limit dBuV/m @3m QP or Average
30MHz-230MHz		40 dBuV/m QP
230MHz-1GHz		47dBuV/m QP
1GHz-3GHz	70dBuV/m Peak	50dBuV/m AV
3GHz-6GHz	74dBuV/m Peak	54dBuV/m AV

Conclusion: If the requirements for radiated emissions according to EN 55022 / CISPR 22 or other standards with the same limits are fulfilled, also the EMF requirements for the measured frequency range are fulfilled



### 3.Result

#### WIFI

Mode	Channel	maximum eirp power (dBm)	maximum eirp power (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm <sup>2</sup> )	Limit of Power Density (S) (mW/ cm <sup>2</sup> )	Result
802.11b	CH13	14.3	26.915	2(1.0dBi)	0.0054	1	Pass
802.11g	CH07	9.5	8.913	2(1.0dBi)	0.0018	1	Pass
802.11n20	CH01	9.7	9.333	2(1.0dBi)	0.0019	1	Pass
802.11n40	CH13	9.6	9.120	2(1.0dBi)	0.0018	1	Pass

Note: The Output power is the maximum eirp power of this EUT, and the data comes from the RF report for this EUT.

Note: The assess distance is 20cm.