

FCC Part 15B Measurement and Test Report

For

SHENZHEN WINTACT ELECTRONICS CO., LTD.

ROOM C,FLOOR 6BLOCK B,DONGFANG JIANFU YIJING

INDUSTRIAL ZONE,GONGMING TOWN,GUANGMING

DISTRICT,SHENZHEN CITY,GUANGDONG PROVINCE,CHINA

FCC Rule(s): FCC Part 15 Subpart B

Product Description: Digital Anemometer

Tested Model: WT82

Report No.: STR18118195E-3

Sample Receipt Date: 2018-11-22

Tested Date: 2018-11-22 to 2018-11-27

Issued Date: 2018-11-27

Tested By: Alan / Engineer

Reviewed By: Silin Chen / EMC Manager

Approved & Authorized By: Jandy So / PSQ Manager

Prepared By:

Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,

Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn



Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY	4
1.4 TEST FACILITY	4
1.5 EUT SETUP AND OPERATION MODE	5
1.6 MEASUREMENT UNCERTAINTY	5
1.7 TEST EQUIPMENT LIST AND DETAILS	6
2. SUMMARY OF TEST RESULTS	7
3. RADIATED EMISSION	8
3.1 TEST PROCEDURE.....	8
3.2 TEST RECEIVER SETUP	8
3.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	9
3.4 ENVIRONMENTAL CONDITIONS	9
3.5 SUMMARY OF TEST RESULTS/PLOTS	9
EXHIBIT 1 - PRODUCT LABELING	12
PROPOSED FCC LABEL FORMAT	12
PROPOSED LABEL LOCATION ON EUT	12
EXHIBIT 2 - EUT PHOTOGRAPHS.....	13
EXHIBIT 3 - EUT INTERNAL PHOTOGRAPHS.....	15
EXHIBIT 4 - TEST SETUP PHOTOGRAPHS	17
EXHIBIT 5 - USERS MANUAL	18

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: SHENZHEN WINTACT ELECTRONICS CO., LTD.
ROOM C,FLOOR 6BLOCK B,DONGFANG JIANFU
YIJING INDUSTRIAL ZONE,GONGMING TOWN,
Address of applicant: GUANGMING DISTRICT,SHENZHEN CITY,
GUANGDONG PROVINCE,CHINA

Manufacturer: SHENZHEN WINTACT ELECTRONICS CO., LTD.
ROOM C,FLOOR 6BLOCK B,DONGFANG JIANFU
YIJING INDUSTRIAL ZONE,GONGMING TOWN,
Address of manufacturer: GUANGMING DISTRICT,SHENZHEN CITY,
GUANGDONG PROVINCE,CHINA

General Description of EUT	
Product Name:	Digital Anemometer
Trade Name:	WINTACT
Model No.:	WT82
Adding Model(s):	WT82B、WT82C、WT82D、WT816、WT816A、 WT9025、WT9026、GM816、GM8901、GM8901+、 GM8902、GM8902+、GM8903、GM8909、GM8907、 GM8908、GM8910、GM8911
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model WT82, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Rated Voltage:	DC 4.5V
Rated Current:	/
Rated Power:	/
Power Adapter Model:	/
Lowest Internal Frequency:	/
Highest Internal Frequency:	Below 108MHz
Classification of ITE:	Class B

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15 Subpart B: Unintentional Radiators

ANSI C63.4-2014: American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List:

Test Mode	Description	Remark	Power Supply Mode
TM1	Working	Battery power	With 3 section 1.5 V battery

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
/	/	/	/

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
Conducted Emissions	Conducted	9-150kHz ± 3.74 dB
		0.15-30MHz ± 3.34 dB
Radiated Emissions	Radiated	30-200MHz ± 4.52 dB
		0.2-1GHz ± 5.56 dB
		1-6GHz ± 3.84 dB
		6-18GHz ± 3.92 dB

1.7 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
Spectrum Analyzer	Agilent	E4407B	MY41440400	2018-05-22	2019-05-21
Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2018-05-22	2019-05-21
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2018-05-22	2019-05-21
Amplifier	Agilent	8447F	3113A06717	2018-05-22	2019-05-21
Amplifier	C&D	PAP-1G18	2002	2018-05-22	2019-05-21
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2018-05-22	2019-05-21
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2018-05-22	2019-05-21
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2018-05-22	2019-05-21

2. SUMMARY OF TEST RESULTS

Description of Test	Result
§15.107 (a) Conducted Emission	N/A
§15.109(a) Radiated Emission	Compliant

N/A: not applicable


3. RADIATED EMISSION

3.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



3.2 Test Receiver Setup

Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

3.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for a Class B device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15.109(a) Limit}$$

3.4 Environmental Conditions


Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	1011 mbar

3.5 Summary of Test Results/Plots

According to the data, the EUT complied with the FCC Part 15.109(a) rule, and had the worst margin of:


-18.63 dB at 709.1823 MHz in the Vertical polarization, TM1 mode, 30MHz to 1 GHz, 3Meters

Test mode:	TM1	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	45.5348	28.84	-11.87	16.97	40.00	-23.03	357	100	QP
2	65.1145	29.05	-14.04	15.01	40.00	-24.99	97	100	QP
3	90.5374	29.63	-13.51	16.12	43.50	-27.38	214	100	QP
4	272.2776	27.79	-9.04	18.75	46.00	-27.25	101	100	QP
5	383.9318	28.35	-7.01	21.34	46.00	-24.66	184	100	QP
6	689.5644	28.64	-2.01	26.63	46.00	-19.37	235	100	QP

Test mode:	TM1	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	50.7637	27.58	-11.59	15.99	40.00	-24.01	231	100	QP
2	89.9047	27.30	-13.47	13.83	43.50	-29.67	90	100	QP
3	239.1473	26.28	-10.11	16.17	46.00	-29.83	85	100	QP
4	301.4224	27.01	-8.17	18.84	46.00	-27.16	97	100	QP
5	515.4374	28.93	-5.43	23.50	46.00	-22.50	203	100	QP
6	709.1823	29.20	-1.83	27.37	46.00	-18.63	313	100	QP

EXHIBIT 1 - PRODUCT LABELING

Proposed FCC Label Format



Specifications: Text is Black in color and is justified. Labels are printed in indelible ink on permanent adhesive backing or silk-screened onto the EUT or shall be affixed at a conspicuous location on the EUT. Where the EUT is constructed in two or more sections connected by wires and marketed together, the above statement is required to be affixed only to the main control unit. When the EUT is so small or for such use that it is not practicable to place the statement on it, the above information shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed.

Proposed Label Location on EUT

FCC Label Location




EXHIBIT 2 - EUT PHOTOGRAPHS

EUT View 1




EUT View 2




EUT View 3

EXHIBIT 3 - EUT INTERNAL PHOTOGRAPHS

EUT Housing and Board View 1



EUT Housing and Board View 2



EUT Housing and Board View 3




EXHIBIT 4 - TEST SETUP PHOTOGRAPHS

Radiation Emission View



EXHIBIT 5 - USERS MANUAL

Information to Users

According to the FCC Part 15.19, 15.21, and 15.105 rules, for this EUT, the instructions or operation manual furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

FCC Caution

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

NOTE 1: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

NOTE 2: Any changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

***** END OF REPORT *****