GF - 07 enhanced magnetic locator

The instructions

Warm prompt: we are in pursuit of quality, practical, sound is clearer, more accurate positioning, standby time is longer, not blindly pursue low-end KengMeng consumers inferior products. Enhanced alarm locator is a base station positioning in a best cost-effective, higher requirements for high-end customers, let you really buy the rest assured, with enjoyable. Not some fake products; Through low inferior chip, the cost is low, quality is not guaranteed.

Product advantage:

1, is the only similar products of all mobile phones on the map to view the query to the location and computer platform position trajectory, also can be directly reply messages in Chinese position.

2. In the first base station positioning on the basis of the original joined Google maps positioning, greatly reduces the error range of the product.

3. Due to the joined Google positioning mode, the product positioning function now support abroad.

4. If we can call 10086 opened around listening to sound more friendship number per month, it's only a number five yuan a month to check how long don't money.

This product does not need to cost platform, life-long free of charge. Just send a
message to the alarm locator, can respond to the following address information in Chinese
and Google maps connection, simple operation, one pace reachs the designated position.
 This product built-in powerful magnet adsorption function, need not you worry again put
problem, as long as there is metal, you can directly put up, the magnet will automatically
adsorption, more convenient installation you put the position

6. This product is the only market with the function of charge automatically boot, connect the power supply, when the alarm locator electricity used up and products after shutdown, call the product will be automatically switched on and continue to recharge, warning, charging must insert SIM card

7. Our website HTTP; / / gpsui.net



Regardless of alarm locator on the cart, children bag, the old man's pocket, valuables bag, can through the mobile phone to send SMS alarm locator, query alarm locator location, convenient you to monitor all the way, to master the location of the object in real time. Method of use:

1. Preparation: a SIM phone card and mini memory card,

2. Boot: open the card cover according to the directions insert SIM card, mini memory card is inserted in, products will be automatically switched on the red light shine out 4 times, 30 seconds to enter standby state.

The indicator light: light is normally on four boot, low battery indicator light flash
 binding master number; Using a mobile phone text 000 sent to alarm the locator number, later the machine reply to phone a message; The set; Binding + master number
 Separate recordings; Using a mobile phone text 555 sent to alarm the locator number, later the machine reply to phone a message; [Snd; recording started]

6. The voice control callback; Using a mobile phone text 666 sent to alarm the locator number, later the machine reply to phone a message; [DT; has been successfully set sound monitor, alarm telephone callback],.

When the sound of the alarm locator around more than 40 db, alarm locator will automatically call set phone number in advance.

7. GPRS location query: edit mobile phone text messages sent to alarm the locator number 777, later reply phone a native Chinese geographical location and Google maps link, location map will be shown after the mobile phone to open the links and text address, make a more accurate location.

Around 8. Product voice query: direct dialing alarm locator card number, after a few seconds to can hear the sound of the alarm locator around (in the query will not make any sound and light alarm locator itself)

9. The location path query; Use their phones to edit text messages sent to alarm the locator number 102, reply later native mobile a/account, password, website HTTP; // gpsui.net

10. Delete the content of the memory CARDS; Use their phones to edit text messages sent to alarm the locator number 445, native reply later phone a [] TF, clean up the success, the current can have capacity

The state of the host; Using a mobile phone text 888 sent to alarm the locator number, later the machine reply to phone a message; [host all the features on or off battery capacity binding number, signal strength, frequency startup, GPRS TF card capacity etc.).
 Restart the host; Using a mobile phone text 999 sent to alarm the locator number, such as 1 minute recovery success.

13. Shut down, the information above are remaining power according to stop function; Use their phones to edit text messages sent to alarm the locator number 444, a native reply later mobile phones and "Reset; all tasks have been cancelled"

14. Electricity query: located in every time you reply,

{this product can also be an external smoke alarm door magnetic shoe bag need to increase the functions such as water or customized products and the suggestion, please contact the dealer}

1. Appearance size: 3.5 cm * 2.0 cm * 1.4 cm (L * W * H)

2. Charging input InputAC110-220 v50/60 hz

3. The charging output: OutputDC5.0 V 300-500 ma

4. The machine battery: 3.7 V 400 mah Li - ion '

5. Standby time: 12 days. Working time 4 to 6 days

- 6. The expansion card; Mini TF card
- 7. The video video; 320 * 240
- 8. The photo size; 640 * 480
- 9. Talk: 150-180 minutes
- 10. Format: GSM/GPRS
- 11.. Storage temperature: 40 ° C to + 85 ° C
- 12. Working temperature 20 ° C to + 55 ° C
- 13. Humidity range 5% 95% non condensing
- 14, GPRS: Upload60, TCP/IP
- 15, working voltage: 3.4-4.2 V DC
- 16 standby current: : material 2.5 mA
- 17, open the acoustic current: material 30 ma
- 18, call: current material 150 ma
- 19, GSM positioning time: 25 seconds

Basic parameters: spectrum GSM850/900/1800/1900 MHZ

Supported countries: China Britain France Germany Netherlands Italy Spain Brazil, Portugal, Denmark Russia Poland Turkey Hungary Thailand Indonesia Malaysia Vietnam myanmar Pakistan, Iraq, Saudi Arabia, Greece the kazakhstan Mongolia dubai, etc...

Often encounter problems:

1. The host can't get through

Answer: must insert SIM boot will enable mobile phone signal, after the mobile phone card, so you only need to turn after the reboot the machine. Still have even if your mobile phone card is not in the server, no signal.

2. TF memory card cannot be stored?

A: check whether the TF memory card is wrong, if there is no question about the TF card can put the TF memory card format to retry.

3 can't charge?

Answer: to charging the GSM card, if you are unable to realize charging is not. 4 what is the main control cell phone?

A: is that you need to use it to monitor and alarm system of mobile phone.

Special warning: when the deficiency of alarm locator (power under 5%) please charge in time, such as the battery is in a state of loss of electricity for a long time, will inevitably cause the battery to discharge depth affect battery performance and life, serious battery charge it into electricity or scrap, such as alarm locator when not in use, please put the battery charged to 60% - 80% disconnect the power of the locator, in storage, not for a long time (three months) please the locator to supplement the electric regularly, in order to protect the battery, in order to you better use this machine, please read and follow the above, thanks