

Model No		SF-3083W
Video	Image Sensor	1/3" Super HAD CCD
	Scanning system	2:1 Interlace
	Total Pixel	PAL:960H*582V NTSC:967H*494V
	Horizontal Resolution	650TVL
	Min. Illumination	0Lux IR On
	S/N Ratio	≧ 52dB
	Video Output	CVBS:1.0Vp-p/75Ω Composite
	Gamma Correction	0.45
	Frequency	H:15.734 KHz/V:15.625KHz/V:50Hz
	Sync. System	Internal Synchronization
	Day&Night	Auto/ Color/ B/W
	Electronic Shutter Speed	1/50 -1/10,000s
	Scanning system	2:1 Interlace
	Operational	White Balance
Backlight Compensation		OFF/BLC/HLC
Mirror		Flip Horizontal
Motion Detection		8 Area Setting
Privacy		8 Area Setting
A.G.C		Auto/Manual
On Screen Display		Chinese,English,French,German,Russian,Japanese,Spanish,Portuguese
Sharpness		On/Off(Level Adjustable)
ATR		On/Off
Noise Reduction		2D-DNR
Defect Cancellation		Static & Dynamic
Camera Title		Off/On (Display 15 Characters)
Lens	IR LED	36 Pcs 5mm IR LED, IR 30m Max.
	Lens Type	4-9mm Varifocal Fixed Iris Lens (Standard)
	MountType	C/CS
Electrical	Power Supply	DC12V ±5%
	Power Consumption	≤2W
Environmental	Work Humidity	≧ 85%RH
	Operation Temperature	-10℃ ~+50℃
Physical	External Case	Aluminum Alloy (Vandal Resistant IP65)
	Dimensions (W*H*L)	85mm x 145mm x 232mm
	Weight	N.W. 0.95kg G.W. 1.05kg