


# KLS-25M

## Mini Size Optical Light Source




## Product Characteristics

- 2.5mm Universal
- Wavelength: SM 1310/1550nm
- MM 850/1300nm
- PON 三波长 1310/1490/1550nm
- Low battery reminder function
- Typical output power:  $\geq -5\text{dBm}$
- Drop protection: 2m
- Water-resistant keys
- LED lighting, clear in the dark environment
- Pocket size design




Backlight display



One-key start



Automatic shutdown



Plug and play



Super long standby



Silicone protective  
case

## Modulation Carrier Output

Continuous output, three modulation frequencies

270Hz

1000Hz

2000Hz



# Singlemode

1310nm+1550nm



## Main Features



Drop protection



Mini Size




Detachable protective sleeve




LED lighting




# KLS-25M




FC



SC



LC(Optional)



ST

|                        |                                             |
|------------------------|---------------------------------------------|
| Wavelength(nm)         | SM 1310/1550nm                              |
|                        | MM 850/1300nm                               |
|                        | PON 三波长 1310/1490/1550nm                    |
| Typical Output Power   | ≥-5dBm                                      |
| Optical Connector      | 2.5mm universal (1.25mm for LC is Optional) |
| Power Supply           | Alkaline Battery(2 AAA 1.5V batteries)      |
| Output Stability       | ±0.05dB/15mins; ±0.1dB/ 8h                  |
| Modulation Frequencies | CW, 270Hz, 1KHz, 2KHz                       |
| Dimensions / Weight    | 130x65x35mm / 180g                          |



## Product Display

